



STATE OF NEVADA

Department of Conservation & Natural Resources

DIVISION OF ENVIRONMENTAL PROTECTION

Jim Gibbons, Governor

Allen Biaggi, Director

Leo M. Drozdoff, P.E., Administrator

February 26, 2009

Mr. Mark Paris
Basic Remediation Company
875 West Warm Springs Road
Henderson, NV 89011

Ms. Susan Crowley
Tronox LLC
PO Box 55
Henderson, NV 89009

Mr. Curt Richards
Olin Corporation
3855 North Ocoee Street, Suite 200,
Cleveland, TN 37312

Mr. Joe Kelly
Montrose Chemical Corp of CA
600 Ericksen Ave NE, Suite 380
Bainbridge Island, WA 98110

Mr. Brian Spiller
Stauffer Management Co LLC
1800 Concord Pike
Wilmington, DE 19850-6438

Mr. Craig Wilkinson
Titanium Metals Corporation
PO Box 2128
Henderson, NV 89009

Re. **BMI Plant Sites and Common Areas Projects, Henderson, Nevada**
Supplemental Guidance on Data Validation

Dear Sirs and Madam:

All of the parties listed above shall be referred to as “the Companies” for the purposes of this letter. As the Companies should be aware, the United States Environmental Protection Agency (USEPA) has issued revisions to the National Functional Guidelines. The Nevada Division of Environmental Protection (NDEP) provides guidance in Attachment A regarding how these revisions should be applied to data validated for the BMI Complex and Common Areas projects.

Please contact me with any questions (tel: 702-486-2850 x247; e-mail: brakvica@ndep.nv.gov).

Sincerely,

Brian A Rakvica, P.E.
Supervisor, Special Projects Branch
Bureau of Corrective Actions
Fax: (702) 486-5733

BAR:s

CC: Jim Najima, NDEP, BCA, Carson City
Marysia Skorska, NDEP, BCA, Las Vegas
Shannon Harbour, NDEP, BCA, Las Vegas
Todd Croft, NDEP, BCA, Las Vegas
Greg Lovato, NDEP, BCA, Carson City
Barry Conaty, Holland & Hart LLP, 975 F Street, N.W., Suite 900, Washington, D.C. 20004
Brenda Pohlmann, City of Henderson, PO Box 95050, Henderson, NV 89009
Mitch Kaplan, U.S. Environmental Protection Agency, Region 9, mail code: WST-5,
75 Hawthorne Street, San Francisco, CA 94105-3901
Ebrahim Juma, Clark County DAQEM, PO Box 551741, Las Vegas, NV, 89155-
1741
Ranajit Sahu, BRC, 311 North Story Place, Alhambra, CA 91801
Rick Kellogg, BRC, 875 West Warm Springs, Henderson, NV 89011
Kirk Stowers, Broadbent & Associates, 8 West Pacific Avenue, Henderson, Nevada 89015
George Crouse, Syngenta Crop Protection, Inc., 410 Swing Road, Greensboro, NC 27409
Nicholas Pogoncheff, PES Environmental, Inc., 1682 Novato Blvd., Suite 100, Novato, CA
94947-7021
Lee Erickson, Stauffer Management Company LLC, P.O. Box 18890 Golden, CO 80402
Keith Bailey, Environmental Answers, 3229 Persimmon Creek Drive, Edmond, OK 73013
Susan Crowley, Crowley Environmental LLC, 366 Esquina Dr., Henderson, NV 89014
Mike Skromyda, Tronox LLC, PO Box 55, Henderson, Nevada 89009
Jeff Gibson, AMPAC, 3770 Howard Hughes Parkway, Suite 300, Las Vegas, Nevada 89109
Sally Bilodeau, ENSR, 1220 Avenida Acaso, Camarillo, CA 93012-8727
Cindi Byrns, Olin Chlor Alkali, PO Box 86, Henderson, Nevada 89009
Paul Sundberg, Montrose Chemical Corporation, 10733 Wave Crest Court
Stockton, CA 95209
Joe Kelly, Montrose Chemical Corporation of CA, 600 Ericksen Avenue NE, Suite 380,
Bainbridge Island, WA 98110
Deni Chambers, Northgate Environmental Management, Inc., 300 Frank H. Ogawa Plaza, Suite
510, Oakland, CA 94612
Robert Infelise, Cox Castle Nicholson, 555 California Street, 10th Floor, San Francisco, CA 94104-1513
Michael Ford, Bryan Cave, One Renaissance Square, Two North Central Avenue, Suite 2200,
Phoenix, AZ 85004
Dave Gratson, Neptune and Company, 1505 15th Street, Suite B, Los Alamos, NM 87544
Paul Black, Neptune and Company, Inc., 8550 West 14th Street, Suite 100, Lakewood, CO 80215
Teri Copeland, 5737 Kanan Rd., #182, Agoura Hills, CA 91301
Paul Hackenberry, Hackenberry Associates, 550 West Plumb Lane, B425, Reno, NV, 89509

Attachment A

Revisions to Data Validation of Organic Data based on June 2008 National Functional Guidelines for Superfund Organic Methods Data Review – USEPA-540-R-08-01.

The USEPA Office of Superfund Remediation and Technology Innovation released an updated version of the National Functional Guidelines (NFG) for Superfund Organic Methods Data Review in June, 2008. These updated guidelines contain several revisions with respect to how data is to be validated under the USEPA Contract Laboratory Program. The Companies currently collecting and validating data at the BMI Complex and Common Areas projects have generally followed these NFGs, though in general earlier versions of the guidance have been followed.

Significant changes to the NFGs are discussed below.

Holding Times

The new USEPA guidance revises the period of time allowed before data are qualified when a holding time has been exceeded.

If VOC data are one day past holding time, non-detects are qualified as unusable (R). Previously this was applied if the holding time was exceeded by a factor of two. The new guidance does not necessarily apply the same level of qualification to semi-volatile, pesticides, and Aroclor fractions. For these analyses the guidance is to qualify as estimated (UJ) or unusable, based on professional judgment, if holding times are exceeded by one day or more.

At this time NDEP recommends the current qualification algorithm (twice the holding time) continue to be used. Studies have shown that most chemicals are stable for that period if the samples are kept cold and preserved where applicable (aqueous samples). However, each time a batch of samples are analyzed past holding time, professional judgment should be used to arrive at the qualification and usability assessment. It is recommended that the Companies use historic results, where holding times were met, along with evidence from compound stability studies to arrive at the final usability assessment.

Sample Receipt Temperatures

The new guidance, which applies to all organic suites (volatile organic compounds (VOCs), semi-VOCs (SVOC), pesticides, and polychlorinated biphenyls (PCBs)), is to use professional judgment if sample coolers arrive at the laboratory below 2 °C or above 6 °C.

No change in the current qualification and usability is proposed by NDEP. Professional judgment should guide this assessment. It is noted that stability studies of volatile compounds indicate a number of the compounds at the site (e.g. chlorinated benzenes) can degrade when not kept cold and preserved. Again, the use of historic results, where cooler temperatures were met, is the best approach for arriving at the final data usability assessment.

Blank Contamination

The new guidance for qualifying VOC results based on blank contamination is provided in the table below with additional details provided in the USEPA guidance -Section E of the Low/Medium Volatiles Data Review. Qualification is based upon a comparison with the associated blank. If an analyte is found in a blank but not in associated samples no qualification is required. For the NDEP’s purposes, the sample quantitation limit (SQL) replaces the USEPA’s Contract Required Quantitation Limit (CRQL).

Blank Type	Blank Result	Sample Result	Action for Samples
Method, Storage, Field, Trip, Instrument	< SQL *	< SQL*	Report SQL value with a U
		≥ SQL*	Use professional judgment
	> SQL *	< SQL*	Report SQL value with a U
		≥SQL* and < blank result	Report the blank result for the sample with a U or qualify the data as unusable R
		≥SQL* and ≥ blank result	Use professional judgment
	= SQL*	< SQL*	Report SQL value with a U
		≥SQL*	Use professional judgment
	Gross contamination	Detects	Qualify results as unusable R

* 2x the SQL for methylene chloride, 2-butanone and acetone.

NDEP recommends that this approach to qualifying VOCs be adopted, with the understanding that SQL replaces USEPA CRQL. It is also important to compare any potential censored results, due to blank contamination, with the applicable standard such as USEPA maximum contaminant levels (MCLs) or NDEP Basic Comparison Levels (BCLs), during the data usability assessment.

The same approach is provided in the guidance for SVOC blank assessment and this also should be adopted. For SVOCs, 5 times the SQL for bis(2-ethylhexyl)phthalate is used. The pesticides and PCB blank analysis does not use a 2X/5X factor but promotes professional judgment for any blank value above the CRQL (SQL) with the potential for qualifying data as unusable (R).

System Monitoring Compounds

The new guidance revises the level where VOC surrogate recovery results in data qualification. If the recovery of a surrogate is < 20%, the “not-detected” results associated with the surrogate are considered unusable (R) and positive results are qualified as estimated. If the recovery is > 20%, but < lower QC limit, the “not-detected” and positive results are qualified as estimated. In the prior guidance the cutoff was 10%.

At this point NDEP does not require changing the cutoff from 10% to 20%. However, professional judgment should be used and problems with system monitoring compounds should be investigated when the recovery is less than 20%.

Matrix Spike/ Matrix Spike Duplicate (MS/MSD)

The prior USEPA guidance did not provide any substantive guidance for a usability assessment based on MS/MSD results. The new USEPA guidance does not recommend qualification based solely on MS/MSD results. However, professional judgment in conjunction with other quality control (QC) results should be considered to qualify results as follows:

The new guidance for VOCs is as follows:

For any recovery or RPD **greater** than the upper QC limit: qualify positive results with a “J”. “Not-detected” results should not be qualified.

For any recovery $\geq 20\%$, and less than the lower QC limit: qualify positive results with a “J”. “Not-detected” results should be qualified “UJ”.

For any recovery $< 20\%$: qualify positive results with a “J.” “Not-detected” results use professional judgment.

At this point NDEP does not require changing the steps for qualifying VOC data based on these revisions to the MS/MSD assessment. Again, professional judgment is important and other QC results should be considered along with MS/MSD results.

Internal Standards

The revision to assessment of internal standards applies to all organics suites in the guidance (VOC, SVOC, pesticides, PCBs). The changes to the guidance are as follows:

If the sample internal standard area is 60% of the associated continuing calibration verification (CCV) internal standard area, positive sample results are qualified as estimated, and “not-detected” sample results are qualified as **unusable (R)**. Also, if the Retention Time of the internal standard differs by more than 20 seconds from the associated CCV, all positive and “not-detected” sample results should be qualified as unusable (R). However, caveats can be used based upon mass spectra criteria and partial rejection.

Internal standards are only assessed during Level IV data validation. This is required for at least 10% of the samples reported in a data validation summary report (DVSR). At this point NDEP feels the cutoff of 60% is not warranted. However, a cutoff point of 25%, using the same logic as above, is recommended.

Percent Moisture

The steps to qualify data based on high levels of percent moisture apply to all organic analysis in the new guidance. The 1999 USEPA guidance had no assessment with respect to percent moisture. The new guidance is:

If the sample percent moisture is $>70\%$ but $<90\%$, qualify positive samples as estimated “J” and “not-detected” samples as estimated “UJ.” If the sample percent moisture is $\geq 90\%$, qualify positive samples as estimated “J” and “not-detected” samples as unusable “R.”

NDEP believes this approach is supported and should be utilizable for all analyses including metals, radionuclides and other inorganic analytes.