



Bureau of Air Pollution Control

901 SOUTH STEWART STREET SUITE 4001

CARSON CITY, NEVADA 89701-5249

p: 775-687-9349 • ndep.nv.gov/air

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. (HEREINAFTER REFERRED TO AS PERMITTEE)

Mailing Address: 1410 W. RAILROAD STREET, WINNEMUCCA, NV 89445

Driving Directions: FROM I-80 WEST, TAKE EXIT 229 FOR STATE ROUTE 305. TRAVEL SOUTHWEST ON STATE ROUTE 305 FOR APPROXIMATELY 7.1 MILES. THE FACILITY IS ON THE RIGHT SIDE, WEST OF 305.

General Facility Location: SECTION 17, T 31 N, R 44 E, MDB&M
HA 59 – LOWER REESE RIVER VALLEY / LANDER COUNTY
NORTH 4,489,902 M, EAST 496,988 M, UTM ZONE 11, NAD 83

Emission Unit List:

A. System 01 – Crushing and Screening – Conveyor Transfers

- PF1.001 Loader Transfer to Grizzly Feeder
- PF1.002 Conveyor C-1 Transfer to Conveyor C-2
- PF1.003 Conveyor C-7 Transfer to Radial Stacker C-8
- PF1.004 Radial Stacker C-8 Transfer to Product Stockpile 1
- PF1.005 Conveyor C-4 Transfer to Conveyor C-5 (Split)
- PF1.006 Conveyor C-4 Transfer to Conveyor C-9 (Split)
- PF1.007 Conveyor C-5 Transfer to Radial Stacker C-6
- PF1.008 Radial Stacker C-6 Transfer to Product Stockpile 2
- PF1.009 Conveyor C-9 Transfer to Conveyor C-10
- PF1.010 Conveyor C-10 Transfer to Conveyor C-11
- PF1.011 Conveyor C-12 Transfer to Conveyor C-13
- PF1.012 Conveyor C-14 Transfer to Conveyor C-10 (Recycle)
- PF1.013 Conveyor C-15 Transfer to Conveyor C-16
- PF1.014 Conveyor C-16 Transfer to Product Stockpile 3
- PF1.015 Conveyor C-17 Transfer to Conveyor C-18
- PF1.016 Conveyor C-18 Transfer to Product Stockpile 4
- PF1.017 Conveyor C-19 Transfer to Conveyor C-20
- PF1.018 Conveyor C-20 Transfer to Radial Stacker C-21
- PF1.019 Radial Stacker C-21 Transfer to Product Stockpile 5

B. System 02 – Crushing and Screening - Crushers

- PF1.020 Primary Crusher CR-1 and Associated Transfers (In: Grizzly Feeder; Out: Conveyor C-1)
- PF1.021 Secondary Crusher CR-2 and Associated Transfers (In: Conveyor C-3; Out: Conveyor C-10)
- PF1.022 Tertiary Crusher CR-3 and Associated Transfers (In: Conveyor C-13; Out: Conveyor C-14)

C. System 03 – Crushing and Screening - Screens

- PF1.023 Primary Screen S-1 and Associated Transfers (In: Conveyor C-2; Out: Conveyor C-3, Conveyor C-4, and Conveyor C-7)
- PF1.024 Secondary Screen and Associated Transfers (In: Conveyor C-11; Out: Conveyor C-12, Conveyor C-15, Conveyor C-17, and Conveyor C-19)

D. System 04 – Lime Marination Plant – Conveyor Transfers

- PF1.025 Loader Transfer to Bin Feeder
- PF1.026 Bin Feeder Transfer to Conveyor C-22
- PF1.027 Conveyor C-22 Transfer to Pugmill
- PF1.028 Pugmill Transfer to Conveyor C-23
- PF1.029 Conveyor C-23 Transfer to Radial Stacker C-24
- PF1.030 Radial Stacker C-24 Transfer to Product Stockpile 6



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Emission Unit List (continued):

E. System 05 – Lime Marination Plant – Lime Silo

- S2.001 Lime Silo Loading
- PF1.031 Lime Silo Unloading to Enclosed Screw Conveyor
- PF1.032 Enclosed Screw Conveyor Transfer to Pugmill

F. System 06 – Asphalt Plant Cold Feed – Conveyor Transfers

- PF1.033 Loader Transfer to 4-Bin Feeder
- PF1.034 4-Bin Feeder Transfer to Conveyor C-25
- PF1.035 Weigh Belt C-26 Transfer to Slinger Belt C-27
- PF1.036 Slinger Belt C-27 Transfer to Drum Dryer

G. System 07 – Asphalt Plant Cold Feed – Scalping Screen

- PF1.037 Scalping Screen S-3 and Associated Transfers (In: Conveyor C-25; Out: Weigh Belt C-26)

H. System 08 – Asphalt Plant Cold Feed – Conveyor Transfers

- PF1.038 Drum Dryer Discharge to Slat Conveyor C-28
- PF1.039 Asphalt Silo Loading
- PF1.040 Asphalt Silo Unloading (Truck Loadout)

I. System 09 – Asphalt Plant – Drum Dryer

- S2.002 Drum Dryer (Diesel-Fired)

J. System 10 – Wash Plant – Conveyor Transfers

- PF1.041 Loader Transfer to Bin Feeder
- PF1.042 Bin Feeder Transfer to Conveyor C-29
- PF1.043 Sand Screw SS-1 Transfer to Radial Stacker C-33
- PF1.044 Radial Stacker C-33 Transfer to Stockpile 7
- PF1.045 Conveyor C-30 Transfer to Stockpile 8
- PF1.046 Conveyor C-31 Transfer to Stockpile 9
- PF1.047 Conveyor C-32 Transfer to Stockpile 10

K. System 11 – Wash Plant – Wash Screen

- PF1.048 Wash Screen S-4 and Associated Transfers (In: Conveyor C-29; Out: Conveyor C-30, Conveyor C-31, Conveyor C-32, and Sand Screw SS-1)

*****End of Emission Unit List*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions

- A. Prohibited acts; penalty; establishment of violation; request for prosecution (NRS 445B.470) (*State Only Requirement*)
1. A person shall not knowingly:
 - a. Violate any applicable provision, the terms or conditions of any permit or any provision for the filing of information;
 - b. Fail to pay any fee;
 - c. Falsify any material statement, representation or certification in any notice or report; or
 - d. Render inaccurate any monitoring device or method, required pursuant to the provisions of NRS 445B.100 to 445B.450, inclusive, or 445B.470 to 445B.640, inclusive, or any regulation adopted pursuant to those provisions.
 2. Any person who violates any provision of subsection 1 shall be punished by a fine of not more than \$10,000 for each day of the violation.
 3. The burden of proof and degree of knowledge required to establish a violation of subsection 1 are the same as those required by 42 U.S.C. § 7413(c), as that section existed on October 1, 1993.
 4. If, in the judgment of the Director of the Department or the Director's designee, any person is engaged in any act or practice which constitutes a criminal offense pursuant to NRS 445B.100 to 445B.640, inclusive, the Director of the Department or the designee may request that the Attorney General or the district attorney of the county in which the criminal offense is alleged to have occurred institute by indictment or information a criminal prosecution of the person.
 5. If, in the judgment of the control officer of a local air pollution control board, any person is engaged in such an act or practice, the control officer may request that the district attorney of the county in which the criminal offense is alleged to have occurred institute by indictment or information a criminal prosecution of the person.
- B. Visible emissions: Maximum opacity; determination and monitoring of opacity (NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
1. Except as otherwise provided in this section and NAC 445B.2202, no owner or operator may cause or permit the discharge into the atmosphere from any emission unit which is of an opacity equal to or greater than 20 percent. Opacity must be determined by one of the following methods:
 - a. If opacity is determined by a visual measurement, it must be determined as set forth in Reference Method 9 in Appendix A of 40 CFR Part 60.
 - b. If a source uses a continuous monitoring system for the measurement of opacity, the data must be reduced to 6-minute averages as set forth in 40 CFR 60.13(h).
 2. The provisions of this section and NAC 445B.2202 do not apply to that part of the opacity that consists of uncombined water. The burden of proof to establish the application of this exemption is upon the person seeking to come within the exemption.
 3. If the provisions of 40 CFR Part 60, Subpart D or Da apply to an emission unit, the emission unit must be allowed one 6-minute period per hour of not more than 27 percent opacity as set forth in 40 CFR 60.42(a)(2) and 40 CFR 60.42a(b).
 4. The continuous monitoring system for monitoring opacity at a facility must be operated and maintained by the owner or operator specified in the permit for the facility in accordance with NAC 445B.256 to 445B.267, inclusive.
- C. Visible emissions: Exceptions for stationary sources (NAC 445B.2202) (*Federally Enforceable SIP Requirement*)
- The provisions of NAC 445B.22017 do not apply to:
1. Smoke from the open burning described in NAC 445B.22067;
 2. Smoke discharged in the course of training air pollution control inspectors to observe visible emissions, if the facility has written approval of the Commission;
 3. Emissions from an incinerator as set forth in NAC 445B.2207; or
 4. Emissions of stationary diesel-powered engines during warm-up for not longer than 15 minutes to achieve operating temperatures.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions (continued)

D. Odors (NAC 445B.22087) (*State Only Requirement*)

1. No person may discharge or cause to be discharged, from any stationary source, any material or regulated air pollutant which is or tends to be offensive to the senses, injurious or detrimental to health and safety, or which in any way interferes with or prevents the comfortable enjoyment of life or property.
2. The Director shall investigate an odor when 30 percent or more of a sample of the people exposed to it believe it to be objectionable in usual places of occupancy. The sample must be at least 20 people or 75 percent of those exposed if fewer than 20 people are exposed.
3. The Director shall deem the odor to be a violation if he or she is able to make two odor measurements within a period of 1 hour. These measurements must be separated by at least 15 minutes. An odor measurement consists of a detectable odor after the odorous air has been diluted with eight or more volumes of odor-free air.

E. Prohibited Conduct: Concealment of Emissions (NAC 445B.225) (*Federally Enforceable SIP Requirement*)

No person may install, construct or use any device which conceals any emission without reducing the total release of regulated air pollutants to the atmosphere.

F. Prohibited conduct: Operation of source without required equipment; removal or modification of required equipment; modification of required procedure (NAC 445B.227) (*Federally Enforceable SIP Requirement*)

Except as otherwise provided in NAC 445B.001 to 445B.3497, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive], no person may:

1. Operate a stationary source of air pollution unless the control equipment for air pollution which is required by applicable requirements or conditions of this Operating Permit is installed and operating.
2. Disconnect, alter, modify or remove any of the control equipment for air pollution or modify any procedure required by an applicable requirement or condition of the permit.

G. Excess Emissions (NAC 445B.232) (*State Only Requirement*)

1. Scheduled maintenance or testing or scheduled repairs which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.3689, inclusive, must be approved in advance by the Director and performed during a time designated by the Director as being favorable for atmospheric ventilation.
2. Each owner or operator shall notify the Director of the proposed time and expected duration at least 30 days before any scheduled maintenance or testing which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.390, inclusive. The scheduled maintenance or testing must not be conducted unless the scheduled maintenance or testing is approved pursuant to subsection 1.
3. Each owner or operator shall notify the Director of the proposed time and expected duration at least 24 hours before any scheduled repairs which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.390, inclusive. The scheduled repairs must not be conducted unless the scheduled repairs are approved pursuant to subsection 1.
4. Each owner or operator shall notify the Director of any excess emissions within 24 hours after any malfunction or upset of the process equipment or equipment for controlling pollution or during start-up or shutdown of that equipment.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions (continued)

G. Excess Emissions (NAC 445B.232) (*State Only Requirement*) (continued)

5. Each owner or operator shall provide the Director, within 15 days after any malfunction, upset, start-up, shutdown or human error which results in excess emissions, sufficient information to enable the Director to determine the seriousness of the excess emissions. The information must include at least the following:
 - a. The identity of the stack or other point of emission, or both, where the excess emissions occurred.
 - b. The estimated magnitude of the excess emissions expressed in opacity or in the units of the applicable limitation on emission and the operating data and methods used in estimating the magnitude of the excess emissions.
 - c. The time and duration of the excess emissions.
 - d. The identity of the equipment causing the excess emissions.
 - e. If the excess emissions were the result of a malfunction, the steps taken to remedy the malfunction and the steps taken or planned to prevent the recurrence of the malfunction.
 - f. The steps taken to limit the excess emissions.
 - g. Documentation that the equipment for controlling air pollution, process equipment or processes were at all times maintained and operated, to a maximum extent practicable, in a manner consistent with good practice for minimizing emissions.
6. Each owner or operator shall ensure that any notification or related information submitted to the Director pursuant to this section is provided in a format specified by the Director.

H. Testing and Sampling (NAC 445B.252) (*Federally Enforceable SIP Requirement*)

1. To determine compliance with NAC 445B.001 to 445B.3497, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive], before the approval or the continuance of an operating permit or similar class of permits, the Director may either conduct or order the owner of any stationary source to conduct or have conducted such testing and sampling as the Director determines necessary. Testing and sampling or either of them must be conducted and the results submitted to the Director within 60 days after achieving the maximum rate of production at which the affected facility will be operated, but not later than 180 days after initial start-up of the facility and at such other times as may be required by the Director.
2. Tests of performance must be conducted and data reduced in accordance with the methods and procedures of the test contained in each applicable subsection of this section unless the Director:
 - a. Specifies or approves, in specific cases, the use of a method of reference with minor changes in methodology;
 - b. Approves the use of an equivalent method;
 - c. Approves the use of an alternative method, the results of which the Director has determined to be adequate for indicating whether a specific stationary source is in compliance; or
 - d. Waives the requirement for tests of performance because the owner or operator of a stationary source has demonstrated by other means to the director's satisfaction that the affected facility is in compliance with the standard.
3. Tests of performance must be conducted under such conditions as the Director specifies to the operator of the plant based on representative performance of the affected facility. The owner or operator shall make available to the Director such records as may be necessary to determine the conditions of the performance test. Operations during periods of startup, shutdown and malfunction must not constitute representative conditions of a performance test unless otherwise specified in the applicable standard.
4. The owner or operator of an affected facility shall give notice to the Director 30 days before the test of performance to allow the Director to have an observer present. A written testing procedure for the test of performance must be submitted to the Director at least 30 days before the test of performance to allow the Director to review the proposed testing procedures.
5. Each test of performance must consist of at least three separate runs using the applicable method for that test. Each run must be conducted for the time and under the conditions specified in the applicable standard. For the purpose of determining compliance with an applicable standard, the arithmetic means of results of the runs apply. In the event of forced shutdown, failure of an irreplaceable portion of the sampling train, extreme meteorological conditions or other circumstances with less than three valid samples being obtained, compliance may be determined using the arithmetic mean of the results of the other two runs upon the Director's approval.
6. All testing and sampling will be performed in accordance with recognized methods and as specified by the Director.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions (continued)

H. Testing and Sampling (NAC 445B.252) (*Federally Enforceable SIP Requirement*) (continued)

7. The cost of all testing and sampling and the cost of all sampling holes, scaffolding, electric power and other pertinent allied facilities as may be required and specified in writing by the Director must be provided and paid for by the owner of the stationary source.
8. All information and analytical results of testing and sampling must be certified as to their truth and accuracy and as to their compliance with all provisions of these regulations, and copies of these results must be provided to the Director no later than 60 days after the testing or sampling, or both.
9. Notwithstanding the provisions of subsection 2, the Director shall not approve an alternative method or equivalent method to determine compliance with a standard or emission limitation contained in Part 60, 61 or 63 of Title 40 of the Code of Federal Regulations for:
 - a. An emission unit that is subject to a testing requirement pursuant to Part 60, 61 or 63 of Title 40 of the Code of Federal Regulations; or
 - b. An affected source.

I. Permit Revision (NAC 445B.287(1)(b)) (*Federally Enforceable SIP Requirement*)

If a stationary source is a Class II source, a revision of the operating permit or the permit to construct is required pursuant to the requirements of NAC 445B.3465 before the stationary source may be modified.

J. Violations: Acts constituting; notice (NAC 445B.275) (*Federally Enforceable SIP Requirement*)

1. Failure to comply with any requirement of NAC 445B.001 to 445B.3791, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive] any applicable requirement or any condition of an operating permit constitutes a violation. As required by NRS 445B.450, the Director shall issue a written notice of an alleged violation to any owner or operator for any violation, including, but not limited to:
 - a. Failure to apply for and obtain an operating permit;
 - b. Failure to construct a stationary source in accordance with the application for an operating permit as approved by the Director;
 - c. Failure to construct or operate a stationary source in accordance with any condition of an operating permit;
 - d. Commencing construction or modification of a stationary source without applying for and receiving an operating permit or a modification of an operating permit as required by NAC 445B.001 to 445B.3497, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.3477, inclusive], or a mercury operating permit to construct as required by NAC 445B.3611 to 445B.3689, inclusive;
 - e. Failure to comply with any requirement for recordkeeping, monitoring, reporting or compliance certification contained in an operating permit; or
 - f. Failure to pay fees as required by NAC 445B.327 or 445B.3689.
2. The written notice must specify the provision of NAC 445B.001 to 445B.3791, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive], the condition of the operating permit or the applicable requirement that is being violated.
3. Written notice shall be deemed to have been served if delivered to the person to whom addressed or if sent by registered or certified mail to the last known address of the person.

K. Operating permits: Imposition of more stringent standards for emissions (NAC 445B.305) (*Federally Enforceable SIP Requirement*)

1. The Director may impose standards for emissions on a proposed stationary source that are more stringent than those found in NAC 445B.001 to 445B.3689, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive], as a condition of approving an operating permit for the proposed stationary source.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions (continued)

L. Contents of operating permits: Exception for operating permits to construct; required conditions (NAC 445B.315)
(*Federally Enforceable SIP Requirement*)

1. Notwithstanding any provision of this section to the contrary, the provisions of this section do not apply to operating permits to construct.
2. The Director shall cite the legal authority for each condition contained in an operating permit.
3. An operating permit must contain the following conditions:
 - a. The term of the operating permit is 5 years.
 - b. The holder of the operating permit shall retain records of all required monitoring data and supporting information for 5 years after the date of the sample collection, measurement, report or analysis. Supporting information includes all records regarding calibration and maintenance of the monitoring equipment and all original strip-chart recordings for continuous monitoring instrumentation.
 - c. Each of the conditions and requirements of the operating permit is severable, and if any are held invalid, the remaining conditions and requirements continue in effect.
 - d. The holder of the operating permit shall comply with all conditions of the operating permit. Any noncompliance constitutes a violation and is a ground for:
 - (1) An action for noncompliance;
 - (2) Revising, revoking, reopening and revising, or terminating the operating permit by the Director; or
 - (3) Denial of an application for a renewal of the operating permit by the Director.
 - e. The need to halt or reduce activity to maintain compliance with the conditions of the operating permit is not a defense to noncompliance with any condition of the operating permit.
 - f. The Director may revise, revoke and reissue, reopen and revise, or terminate the operating permit for cause.
 - g. The operating permit does not convey any property rights or any exclusive privilege.
 - h. The holder of the operating permit shall provide the Director, in writing and within a reasonable time, with any information that the Director requests to determine whether cause exists for revising, revoking and reissuing, reopening and revising, or terminating the operating permit, or to determine compliance with the conditions of the operating permit.
 - i. The holder of the operating permit shall pay fees to the Director in accordance with the provisions set forth in NAC 445B.327 and 445B.331.
 - j. The holder of the operating permit shall allow the Director or any authorized representative, upon presentation of credentials, to:
 - (1) Enter upon the premises of the holder of the operating permit where:
 - (a) The stationary source is located;
 - (b) Activity related to emissions is conducted; or
 - (c) Records are kept pursuant to the conditions of the operating permit;
 - (2) Have access to and copy, during normal business hours, any records that are kept pursuant to the conditions of the operating permit;
 - (3) Inspect, at reasonable times, any facilities, practices, operations or equipment, including any equipment for monitoring or controlling air pollution, that are regulated or required pursuant to the operating permit; and
 - (4) Sample or monitor, at reasonable times, substances or parameters to determine compliance with the conditions of the operating permit or applicable requirements.
 - k. A responsible official of the stationary source shall certify that, based on information and belief formed after a reasonable inquiry, the statements made in any document required to be submitted by any condition of the operating permit are true, accurate and complete.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section I. General Provisions (continued)

M. Operating permits: Assertion of emergency as affirmative defense to action for noncompliance (NAC 445B.326) (*State Only Requirement*)

1. A holder of an operating permit may assert an affirmative defense to an action brought for noncompliance with a technology-based emission limitation contained in the operating permit if the holder of the operating permit demonstrates through signed, contemporaneous operating logs or other relevant evidence, that:
 - a. An emergency occurred and the holder of the operating permit can identify the cause of the emergency;
 - b. The facility was being properly operated at the time of the emergency;
 - c. During the emergency, the holder of the operating permit took all reasonable steps to minimize excess emissions; and
 - d. The holder of the operating permit submitted notice of the emergency to the Director within 2 working days after the emergency. The notice must contain a description of the emergency, any steps taken to mitigate emissions, and any corrective actions taken to restore the normal operation of the facility.
2. In any action for noncompliance, the holder of an operating permit who asserts the affirmative defense of an emergency has the burden of proof.

N. Operating permits: Revocation and reissuance (NAC 445B.3265) (*State Only Requirement*)

1. An operating permit may be revoked if the control equipment is not operating.
2. An operating permit may be revoked by the Director upon determining that there has been a violation of NAC 445B.001 to 445B.390, inclusive, or the provisions of 40 CFR 52.21, or 40 CFR Part 60 or 61, Prevention of Significant Deterioration, New Source Performance Standards, and National Emission Standards for Hazardous Air Pollutants, adopted by reference in NAC 445B.221.
3. The revocation is effective 10 days after the service of a written notice, unless a hearing is requested.
4. To reissue a revoked operating permit, the holder of the revoked permit must file a new application with the Director, accompanied by the fee for an initial operating permit as specified in NAC 445B.327. An environmental review of the stationary source must be conducted as though construction had not yet commenced.

O. Required contents of permit (NAC 445B.346) (*Federally Enforceable SIP Requirement*)

In addition to the conditions set forth in NAC 445B.315, Class II operating permits must contain, as applicable:

1. Emission limitations and standards, including those operational requirements and limitations that ensure compliance with the conditions of the operating permit.
2. All requirements for monitoring, testing and reporting that apply to the stationary source.
3. A requirement that the owner or operator of the stationary source promptly report any deviations from any requirements of the operating permit.
4. The terms and conditions for any reasonably anticipated alternative operating scenarios identified by the owner or operator of the stationary source in his or her application and approved by the Director. Such terms and conditions must require the owner or operator to keep a contemporaneous log of changes from one alternative operating scenario to another.
5. A schedule of compliance for stationary sources that are not in compliance with any applicable requirement or NAC 445B.001 to 445B.3689, inclusive, [NAC adopted as of October 2016 includes NAC 445B.001 to 445B.390, inclusive], at the time the operating permit is issued, including:
 - a. Semiannual progress reports and a schedule of dates for achieving milestones;
 - b. Prior notice of and explanations for missed deadlines; and
 - c. Any preventive or corrective measures taken.

*****End of General Provisions*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section II. General Monitoring, Recordkeeping, and Reporting Conditions

- A. Records Retention (NAC 445B.315(3)(b)) (*Federally Enforceable SIP Requirement*)
The holder of the operating permit shall retain records of all required monitoring data and supporting information for 5 years after the date of the sample collection, measurement, report or analysis. Supporting information includes all records regarding calibration and maintenance of the monitoring equipment and all original strip-chart recordings for continuous monitoring instrumentation.
- B. Deviations (NAC 445B.346(3)) (*Federally Enforceable SIP Requirement*)
Under the authority of NAC 445B.346(3), and in addition to the conditions set forth in NAC 445B.315, the owner or operator of the stationary source shall promptly report to the Director any deviations from the requirements of the operating permit. The report to the Director shall include the probable cause of all deviations and any action taken to correct the deviations. For the operating permit, prompt is defined as submittal of a report within 15 days of the deviation. This definition does not alter any reporting requirements as established for reporting of excess emissions as required under NAC 445B.232 as reproduced in **Section I.G.**
E-mail notifications to: aircompliance@ndep.nv.gov
- C. Yearly Reports (NAC 445B.315(3)(h), NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
Under the authority of NAC 445B.315(3)(h) and NAC 445B.346(2), the Permittee will submit yearly reports including, but not limited to, throughput, production, fuel consumption, hours of operation, and emissions. These reports will be submitted on the form provided by the Bureau of Air Pollution Control for all emission units/systems specified on the form. The completed form must be submitted to the Bureau of Air Pollution Control no later than March 1 annually for the preceding calendar year.

*****End of General Monitoring, Recordkeeping, and Reporting Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section III. General Construction Conditions

A. Notification (NAC 445B.250; NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

Under the authority of NAC 445B.250 and NAC 445B.346; the Director shall be notified in writing of the following for **PF1.036 and PF1.044**:

1. The date construction (or reconstruction as defined under NAC 445B.247) of the affected facility is commenced, postmarked no later than 30 days after such date. This requirement shall not apply in the case of mass-produced facilities which are purchased in completed form.
2. The anticipated date of initial startup of an affected facility, postmarked no more than 60 days and no less than 30 days prior to such date.
3. The actual date of initial startup of the affected facility, postmarked within 15 days after such date.
4. The date upon which demonstration of the continuous monitoring system performance commences in accordance with NAC 445B.256 to 445B.267, inclusive. Notification must be postmarked not less than 30 days before such date.

*****End of General Construction Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section IV. Specific Construction Requirements

A. Initial Opacity Compliance Demonstration and Initial Performance Tests (NAC 445B.22017, NAC 445B.252, NAC 445B.346(2))
(*Federally Enforceable SIP Requirement*)

1. Under the authority of NAC 445B.22017, NAC 445B.252, and NAC 445B.346, the Permittee, upon issuance of this operating permit, shall conduct initial opacity compliance demonstrations and initial performance tests within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup. The Permittee shall follow the test methods and procedures referenced in Table IV-1 and Table IV-2 below:

System	Emission Unit(s)	Pollutant To Be Tested	Testing Methods/Procedures
System 01 – Crushing and Screening – Conveyor Transfers	PF1.001 through PF1.019	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.
System 02 – Crushing and Screening – Crushers	PF1.020 through PF1.022		
System 03 – Crushing and Screening – Screens	PF1.023 and PF1.024		
System 04 – Lime Marination Plant – Conveyor Transfers	PF1.025 through PF1.030		
System 06 – Asphalt Plant Cold Feed – Conveyor Transfers	PF1.033 through PF1.036		
System 07 – Asphalt Plant Cold Feed – Scalping Screen	PF1.037		
System 08 – Asphalt Plant Cold Feed – Conveyor Transfers	PF1.038 through PF1.040		
System 09 – Asphalt Plant – Drum Dryer	S2.002		
System 10 – Wash Plant – Conveyor Transfers	PF1.041 through PF1.047		
System 11 – Wash Plant – Wash Screen	PF1.048		



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section IV. Specific Construction Requirements (continued)

A. Initial Opacity Compliance Demonstration and Initial Performance Tests (NAC 445B.22017, NAC 445B.252, NAC 445B.346(2))
(Federally Enforceable SIP Requirement) (continued)

Table IV-2: Initial Performance Tests

System	Emission Unit(s)	Pollutants To Be Tested	Testing Methods/Procedures
System 02 – Asphalt Plant – Drum Dryer	S2.002	PM	Method 5 in Appendix A of 40 CFR Part 60 shall be used to determine PM emissions. The sample volume for each test run shall be at least 1.7 dscm (60 dscf). Test runs must be conducted for up to two hours in an effort to collect this minimum sample.
		PM ₁₀ /PM _{2.5}	Method 201A and Method 202 in Appendix M of 40 CFR Part 51 shall be used to determine PM ₁₀ and PM _{2.5} emissions. The sample time and sample volume collected for each test run shall be sufficient to collect enough mass to weigh accurately. The Method 201A and 202 test required in this section may be replaced by a Method 5 in Appendix A of 40 CFR Part 60 and Method 202 in Appendix M of 40 CFR Part 51 test. All particulate captured in the Method 5 and Method 202 test performed under this provision shall be considered PM _{2.5} for determination of compliance.
		SO ₂	Method 6C in Appendix A of 40 CFR Part 60 shall be used to determine the sulfur dioxide concentration. Each test will be run for a minimum of one hour.
		NO _x	Method 7E in Appendix A of 40 CFR Part 60 shall be used to determine the nitrogen oxides concentration. Each test will be run for a minimum of one hour.
		CO	Method 10 in Appendix A of 40 CFR Part 60 shall be used to determine the carbon monoxide concentration. Each test will be run for a minimum of one hour.
		VOC	Method 25A in Appendix A of 40 CFR Part 60 shall be used to determine the volatile organic compound concentration. Method 18 in Appendix A of 40 CFR Part 60 or Method 320 in Appendix A of CFR Part 63 may be used in conjunction with Method 25A to break out the organic compounds that are not considered VOC's by definition per 40 CFR 51.100(s). Each Method 25A test will be run for a minimum of one hour.

2. All initial opacity compliance demonstrations and initial performance tests must comply with the advance notification, protocol review, operational conditions, reporting, and other requirements of **Section I.H.** Testing and Sampling (NAC 445B.252) of this operating permit. Material sampling must be conducted in accordance with protocols approved by the Director. All initial performance test results shall be based on the arithmetic average of three valid runs. (NAC 445B.252(5))
3. Testing shall be conducted on the exhaust stack (post controls).
4. Initial opacity compliance demonstrations and initial performance tests, as specified in Table IV-1 and Table IV-2 above, must be conducted under such conditions as the Director specifies to the operator of the plant based on representative performance of the affected facility. The Permittee shall make available to the Director such records as may be necessary to determine the conditions of the initial opacity compliance demonstrations and initial performance tests. Operations during periods of startup, shutdown and malfunction must not constitute representative conditions of the initial opacity compliance demonstrations and initial performance tests unless otherwise specified in the applicable standard. (NAC 445B.252(3))
5. The Permittee shall give notice to the Director 30 days before the initial opacity compliance demonstrations and initial performance tests to allow the Director to have an observer present. A written testing procedure must be submitted to the Director at least 30 days before the initial opacity compliance demonstrations and initial performance tests to allow the Director to review the proposed testing procedures. (NAC 445B.252(4) and 40 CFR Part 60.7(a)(6))
6. Within 60 days after completing the initial opacity compliance demonstrations and initial performance tests contained in Table IV-1 and Table IV-2 of this section, the Permittee shall furnish the Director a written report of the results. All information and analytical results of testing and sampling must be certified as to the truth and accuracy and as to their compliance with NAC 445B.001 to 445B.3689, inclusive. (NAC 445B.252(8))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section IV. Specific Construction Requirements (continued)

A. Initial Opacity Compliance Demonstration and Initial Performance Tests (NAC 445B.22017, NAC 445B.252, NAC 445B.346(2))
(*Federally Enforceable SIP Requirement*) (continued)

7. Initial opacity compliance demonstrations and initial performance tests required under this section that are conducted below the maximum allowable throughput, shall be subject to the Director's review to determine if the throughputs during the initial opacity compliance demonstrations and initial performance tests were sufficient to provide adequate compliance demonstration. Should the Director determine that the initial opacity compliance demonstrations and initial performance tests do not provide adequate compliance demonstration, the Director may require additional testing.

*****End of Specific Construction Requirements*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions

A. Emission Units PF1.001 through PF1.019

System 01 – Crushing and Screening – Conveyor Transfers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.001	Loader Transfer to Grizzly Feeder	4,490,102	496,650
PF1.002	Conveyor C-1 Transfer to Conveyor C-2	4,490,101	496,657
PF1.003	Conveyor C-7 Transfer to Radial Stacker C-8	4,490,105	496,663
PF1.004	Radial Stacker C-8 Transfer to Product Stockpile 1	4,490,116	496,664
PF1.005	Conveyor C-4 Transfer to Conveyor C-5 (Split)	4,490,100	496,665
PF1.006	Conveyor C-4 Transfer to Conveyor C-9 (Split)	4,490,100	496,665
PF1.007	Conveyor C-5 Transfer to Radial Stacker C-6	4,490,107	496,673
PF1.008	Radial Stacker C-6 Transfer to Product Stockpile 2	4,490,114	496,680
PF1.009	Conveyor C-9 Transfer to Conveyor C-10	4,490,097	496,665
PF1.010	Conveyor C-10 Transfer to Conveyor C-11	4,490,097	496,668
PF1.011	Conveyor C-12 Transfer to Conveyor C-13	4,490,091	496,666
PF1.012	Conveyor C-14 Transfer to Conveyor C-10 (Recycle)	4,490,097	496,666
PF1.013	Conveyor C-15 Transfer to Conveyor C-16	4,490,092	496,671
PF1.014	Conveyor C-16 Transfer to Product Stockpile 3	4,490,097	496,684
PF1.015	Conveyor C-17 Transfer to Conveyor C-18	4,490,091	496,670
PF1.016	Conveyor C-18 Transfer to Product Stockpile 4	4,490,085	496,684
PF1.017	Conveyor C-19 Transfer to Conveyor C-20	4,490,091	496,668
PF1.018	Conveyor C-20 Transfer to Radial Stacker C-21	4,490,085	496,667
PF1.019	Radial Stacker C-21 Transfer to Product Stockpile 5	4,490,075	496,667

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. **PF1.001** has no add-on controls.
 - b. Emissions from **PF1.002 through PF1.019, each**, shall be controlled by **water sprays**.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.001 through PF1.019, each**, shall not exceed **450.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **350,000.0** tons per year.
 - b. Hours
 - (1) **PF1.001 through PF1.019, each**, may operate a total of **16** hours per day.
 - (2) **PF1.001 through PF1.019, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.001** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **1.35** pounds per hour, nor more than **0.53** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.50** pounds per hour, nor more than **0.19** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.075** pounds per hour, nor more than **0.029** tons per year.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

A. Emission Units PF1.001 through PF1.019 (continued)

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*) (continued)
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.002 through PF1.019, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.063** pounds per hour, nor more than **0.025** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.021** pounds per hour, nor more than **0.0081** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0059** pounds per hour, nor more than **0.0023** tons per year.
 - c. The opacity from **PF1.001, PF1.004, PF1.008, PF1.014, PF1.016, and PF1.019, each**, shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

 - a. Monitor and record the throughput for **PF1.001 through PF1.019, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.001 through PF1.019, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.002 through PF1.019, each**, on a monthly basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform monthly periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.
 - h. The Permittee, upon issuance of this operating permit, shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative. (40 CFR 60.7(b))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

A. Emission Units PF1.001 through PF1.019 (continued)

5. Federal Requirements (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
New Source Performance Standards (NSPS) – 40 CFR Part 60 Subpart OOO – Standards of Performance for Nonmetallic Mineral Processing Plants (40 CFR Part 60.670)
 - a. Emission Limits (40 CFR Part 60.672, Table 3)

On and after the sixtieth day after achieving the maximum production rate at which **PF1.002, PF1.003, PF1.005 through PF1.007, PF1.009 through PF1.013, PF1.015, PF1.017, and PF1.018, each**, will be operated, but not later than 180 days after initial startup, the Permittee shall not discharge or cause the discharge into the atmosphere, the following pollutants in excess of the following specified limits:

 - (1) Process fugitive emissions from **PF1.002, PF1.003, PF1.005 through PF1.007, PF1.009 through PF1.013, PF1.015, PF1.017, and PF1.018, each**, will not exceed **7 percent** opacity. (40 CFR Part 60.672(b))
 - (2) The opacity standard set forth in this part shall apply at all times except during period of startup, shutdown, and malfunction, and as otherwise provided in the applicable standard. (40 CFR 60.11(c))
 - b. The owner or operator of any affected facility for which construction, modification, or reconstruction commenced on or after April 22, 2008, that uses wet suppression to control emissions from the affected facility must perform monthly periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The owner or operator must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the owner or operator finds that water is not flowing properly during an inspection of the water spray nozzles. The owner or operator must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken, in the logbook required under 40 CFR 60.676(b). (40 CFR 60.674(b))
 - c. Notifications and reports required under this subpart and under subpart A of this part to demonstrate compliance with this subpart need only to be sent to the EPA Region or the State which has been delegated authority according to 40 CFR 60.4(b). (40 CFR 60.676(k))
 - d. At all times, including periods of startup, shutdown, and malfunction, Permittee shall, to the extent practicable, maintain and operate **PF1.002, PF1.003, PF1.005 through PF1.007, PF1.009 through PF1.013, PF1.015, PF1.017, and PF1.018, each**, including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR Part 60.11(d))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

B. Emission Units PF1.020 through PF1.021

System 02 – Crushing and Screening - Crushers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.020	Primary Crusher CR-1 and Associated Transfers (In: Grizzly Feeder; Out: Conveyor C-1)	4,490,102	496,650
PF1.021	Secondary Crusher CR-2 and Associated Transfers (In: Conveyor C-3; Out: Conveyor C-10)	4,490,098	496,663
PF1.022	Tertiary Crusher CR-3 and Associated Transfers (In: Conveyor C-13; Out: Conveyor C-14)	4,490,093	496,666

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
Emissions from **PF1.020 through PF1.022, each**, shall be controlled by **water sprays**.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.020 through PF1.022, each**, shall not exceed **450.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **350,000.0** tons per year.
 - b. Hours
 - (1) **PF1.020 through PF1.022, each**, may operate a total of **16** hours per day.
 - (2) **PF1.020 through PF1.022, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.020 through PF1.022, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.54** pounds per hour, nor more than **0.21** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.24** pounds per hour, nor more than **0.095** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.045** pounds per hour, nor more than **0.018** tons per year.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.020 through PF1.022, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.020 through PF1.022, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.020 through PF1.022, each**, on a monthly basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

B. Emission Units PF1.020 through PF1.021 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*) (continued)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate. (continued)
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform monthly periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expediently as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.
 - h. The Permittee, upon issuance of this operating permit, shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative. (40 CFR 60.7(b))

5. Federal Requirements (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
New Source Performance Standards (NSPS) – 40 CFR Part 60 Subpart OOO – Standards of Performance for Nonmetallic Mineral Processing Plants (40 CFR Part 60.670)
 - a. Emission Limits (40 CFR Part 60.672, Table 3)
On and after the sixtieth day after achieving the maximum production rate at which **PF1.020 through PF1.021, each**, will be operated, but not later than 180 days after initial startup, the Permittee shall not discharge or cause the discharge into the atmosphere, the following pollutants in excess of the following specified limits:
 - (1) Process fugitive emissions from **PF1.020 through PF1.021, each**, will not exceed **12 percent** opacity. (40 CFR Part 60.672(b))
 - (2) The opacity standard set forth in this part shall apply at all times except during period of startup, shutdown, and malfunction, and as otherwise provided in the applicable standard. (40 CFR 60.11(c))
 - b. The owner or operator of any affected facility for which construction, modification, or reconstruction commenced on or after April 22, 2008, that uses wet suppression to control emissions from the affected facility must perform monthly periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The owner or operator must initiate corrective action within 24 hours and complete corrective action as expediently as practical if the owner or operator finds that water is not flowing properly during an inspection of the water spray nozzles. The owner or operator must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken, in the logbook required under 40 CFR 60.676(b). (40 CFR 60.674(b))
 - c. Notifications and reports required under this subpart and under subpart A of this part to demonstrate compliance with this subpart need only to be sent to the EPA Region or the State which has been delegated authority according to 40 CFR 60.4(b). (40 CFR 60.676(k))
 - d. At all times, including periods of startup, shutdown, and malfunction, Permittee shall, to the extent practicable, maintain and operate **PF1.020 through PF1.021, each**, including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR Part 60.11(d))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

C. Emission Units PF1.023 and PF1.024

Table with 4 columns: System 03 - Crushing and Screening - Screens, Location UTM (Zone 11, NAD 83) m North, Location UTM (Zone 11, NAD 83) m East, and rows for PF1.023 and PF1.024.

- 1. Air Pollution Control Equipment (NAC 445B.346(1)) (Federally Enforceable SIP Requirement) Emissions from PF1.023 and PF1.024, each, shall be controlled by water sprays.
2. Operating Parameters (NAC 445B.346(1)) (Federally Enforceable SIP Requirement) a. The maximum allowable throughput rate for PF1.023 and PF1.024, each, shall not exceed 450.0 tons of aggregate per any one-hour period averaged over a daily basis, nor more than 350,000.0 tons per year. b. Hours (1) PF1.023 and PF1.024, each, may operate a total of 16 hours per day. (2) PF1.023 and PF1.024, each, may operate a total of 5,840 hours per year.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1)) (Federally Enforceable SIP Requirement) The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from PF1.023 and PF1.024, each, the following pollutants in excess of the following specified limits: a. The discharge of PM (particulate matter) to the atmosphere shall not exceed 0.99 pounds per hour, nor more than 0.39 tons per year. b. The discharge of PM10 (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed 0.33 pounds per hour, nor more than 0.13 tons per year. c. The discharge of PM2.5 (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed 0.023 pounds per hour, nor more than 0.0088 tons per year.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (Federally Enforceable SIP Requirement) The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate. a. Monitor and record the throughput for PF1.023 and PF1.024, each, on a daily basis. b. Monitor and record the hours of operation for PF1.023 and PF1.024, each, on a daily basis. c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation. d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year. e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year. f. Conduct and record an observation of visible emissions (excluding water vapor) on PF1.023 and PF1.024, each, on a monthly basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

C. Emission Units PF1.023 and PF1.024 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*) (continued)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate. (continued)
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform **monthly** periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.
 - h. The Permittee, upon issuance of this operating permit, shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative. (40 CFR 60.7(b))

5. Federal Requirements (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
New Source Performance Standards (NSPS) – 40 CFR Part 60 Subpart OOO – Standards of Performance for Nonmetallic Mineral Processing Plants (40 CFR Part 60.670)
 - a. Emission Limits (40 CFR Part 60.672, Table 3)
On and after the sixtieth day after achieving the maximum production rate at which **PF1.023 and PF1.024, each**, will be operated, but not later than 180 days after initial startup, the Permittee shall not discharge or cause the discharge into the atmosphere, the following pollutants in excess of the following specified limits:
 - (1) Process fugitive emissions from **PF1.023 and PF1.024, each**, will not exceed **7 percent** opacity. (40 CFR Part 60.672(b))
 - (2) The opacity standard set forth in this part shall apply at all times except during period of startup, shutdown, and malfunction, and as otherwise provided in the applicable standard. (40 CFR 60.11(c))
 - b. The owner or operator of any affected facility for which construction, modification, or reconstruction commenced on or after April 22, 2008, that uses wet suppression to control emissions from the affected facility must perform monthly periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The owner or operator must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the owner or operator finds that water is not flowing properly during an inspection of the water spray nozzles. The owner or operator must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken, in the logbook required under 40 CFR 60.676(b). (40 CFR 60.674(b))
 - c. Notifications and reports required under this subpart and under subpart A of this part to demonstrate compliance with this subpart need only to be sent to the EPA Region or the State which has been delegated authority according to 40 CFR 60.4(b). (40 CFR 60.676(k))
 - d. At all times, including periods of startup, shutdown, and malfunction, Permittee shall, to the extent practicable, maintain and operate **PF1.023 and PF1.024, each**, including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR Part 60.11(d))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

D. Emission Units PF1.025 through PF1.030

System 04 – Lime Marination Plant – Conveyor Transfers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.025	Loader Transfer to Bin Feeder	4,490,013	496,948
PF1.026	Bin Feeder Transfer to Conveyor C-22	4,490,013	496,948
PF1.027	Conveyor C-22 Transfer to Pugmill	4,490,006	496,949
PF1.028	Pugmill Transfer to Conveyor C-23	4,490,006	496,949
PF1.029	Conveyor C-23 Transfer to Radial Stacker C-24	4,489,995	496,950
PF1.030	Radial Stacker C-24 Transfer to Product Stockpile 6	4,489,976	496,961

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. **PF1.025 and PF1.026, each**, have no add-on controls.
 - b. Emissions from **PF1.027 through PF1.030, each**, shall be controlled by **water sprays**.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.025 through PF1.027, each**, shall not exceed **294.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - b. The maximum allowable throughput rate for **PF1.028 through PF1.030, each**, shall not exceed **300.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - c. Hours
 - (1) **PF1.025 through PF1.030, each**, may operate a total of **16** hours per day.
 - (2) **PF1.025 through PF1.030, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.025 and PF1.026, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.88** pounds per hour, nor more than **0.15** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.32** pounds per hour, nor more than **0.055** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.049** pounds per hour, nor more than **0.0083** tons per year.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.027** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.042** pounds per hour, nor more than **0.0070** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.014** pounds per hour, nor more than **0.0023** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0039** pounds per hour, nor more than **0.00065** tons per year.
 - c. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.028 through PF1.030, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.042** pounds per hour, nor more than **0.0070** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.014** pounds per hour, nor more than **0.0023** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0039** pounds per hour, nor more than **0.00065** tons per year.
 - d. The opacity from **PF1.025 through PF1.030, each**, shall not equal or exceed **20** percent.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

D. Emission Units PF1.025 through PF1.030 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **PF1.025 through PF1.030, each**, on a daily basis.
- b. Monitor and record the hours of operation for **PF1.025 through PF1.030, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

E. Emission Units S2.001, PF1.031, and PF1.032

System 05 – Lime Marination Plant – Lime Silo		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.001	Lime Silo Loading	4,490,006	496,946
PF1.031	Lime Silo Unloading to Enclosed Screw Conveyor	4,490,006	496,949
PF1.032	Enclosed Screw Conveyor Transfer to Pugmill	4,490,006	496,946

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.001** shall be controlled by a **baghouse**.
 - b. **PF1.031 and PF1.032, each**, have no add-on controls.
 - c. Descriptive Stack Parameters for S2.001
 Stack Height: 40.0 feet
 Stack Diameter: 2.0 feet
 Stack Temperature: 70 °F

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.001** shall not exceed **24.0** tons of **lime** per any one-hour period, nor more than **5,000.0** tons per year.
 - b. The maximum allowable throughput rate for **PF1.031 and PF1.032, each**, shall not exceed **6.0** tons of **aggregate and lime** per any one-hour period, nor more than **5,000.0** tons per year.
 - c. Hours
 - (1) **S2.001, PF1.031, and PF1.032, each**, may operate a total of **16** hours per day.
 - (2) **S2.001, PF1.031, and PF1.032, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.001** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.024** pounds per hour, nor more than **0.0025** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.0082** pounds per hour, nor more than **0.00085** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0012** pounds per hour, nor more than **0.00013** tons per year.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.031 and PF1.032, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.029** pounds per hour, nor more than **0.012** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.017** pounds per hour, nor more than **0.0070** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0025** pounds per hour, nor more than **0.0011** tons per year.
 - c. The opacity from **S2.001, PF1.031, and PF1.032, each**, shall not equal or exceed **20** percent.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

E. Emission Units S2.001, PF1.031, and PF1.032 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **S2.001, PF1.031, and PF1.032, each**, on a daily basis.
- b. Monitor and record the hours of operation for **S2.001, PF1.031, and PF1.032, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
- f. Conduct and record an observation of visible emissions (excluding water vapor) on the baghouse controlling **S2.001** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- g. Inspect the baghouse installed on **S2.001** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

F. Emission Units PF1.033 through PF1.036

System 06 – Asphalt Plant Cold Feed – Conveyor Transfers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.033	Loader Transfer to 4-Bin Feeder	4,489,928	497,052
PF1.034	4-Bin Feeder Transfer to Conveyor C-25	4,489,928	497,052
PF1.035	Weigh Belt C-26 Transfer to Slinger Belt C-27	4,489,909	497,052
PF1.036	Slinger Belt C-27 Transfer to Drum Dryer	4,489,895	497,036

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. **PF1.033** has no add-on controls.
 - b. Emissions from **PF1.034 through PF1.036, each**, shall be controlled by **water sprays**.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.033 through PF1.036, each**, shall not exceed **285.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - b. Hours
 - (1) **PF1.033 through PF1.036, each**, may operate a total of **16** hours per day.
 - (2) **PF1.033 through PF1.036, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.033** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.86** pounds per hour, nor more than **0.15** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.31** pounds per hour, nor more than **0.055** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.047** pounds per hour, nor more than **0.0083** tons per year.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.034 through PF1.036, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.040** pounds per hour, nor more than **0.0070** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.013** pounds per hour, nor more than **0.0023** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0037** pounds per hour, nor more than **0.00065** tons per year.
 - c. The opacity from **PF1.033 through PF1.036, each**, shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

 - a. Monitor and record the throughput for **PF1.033 through PF1.036, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.033 through PF1.036, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

F. Emission Units PF1.033 through PF1.036 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*) (continued)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate. (continued)
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.034 through PF1.036, each**, on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform **monthly** periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

G. Emission Unit PF1.037

System 07 – Asphalt Plant Cold Feed – Scalping Screen		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.037	Scalping Screen S-3 and Associated Transfers (In: Conveyor C-25; Out: Weigh Belt C-26)	4,489,919	497,041

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
Emissions from **PF1.037** shall be controlled by **water sprays**.
2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.037** shall not exceed **285.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - b. Hours
 - (1) **PF1.037** may operate a total of **16** hours per day.
 - (2) **PF1.037** may operate a total of **5,840** hours per year.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.037** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.63** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.21** pounds per hour, nor more than **0.037** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.014** pounds per hour, nor more than **0.0025** tons per year.
 - d. The opacity from **PF1.037** shall not equal or exceed **20** percent.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.037** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.037** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.037** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

G. Emission Unit PF1.037 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*) (continued)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate. (continued)
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform **monthly** periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.

DRAFT



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

H. Emission Units PF1.038 through PF1.040

System 08 – Asphalt Plant Cold Feed – Conveyor Transfers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.038	Drum Dryer Discharge to Slat Conveyor C-28	4,489,885	497,022
PF1.039	Asphalt Silo Loading	4,489,874	497,017
PF1.040	Asphalt Silo Unloading (Truck Loadout)	4,489,874	497,017

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.038 through PF1.040, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.038 through PF1.040, each**, shall not exceed **300.0** tons of asphalt per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - b. Hours
 - (1) **PF1.038 through PF1.040, each**, may operate a total of **16** hours per day.
 - (2) **PF1.038 through PF1.040, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.038** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (4) The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **0.40** pounds per hour, nor more than **0.067** tons per year.
 - (5) The discharge of **VOC** (volatile organic compound) to the atmosphere shall not exceed **1.25** pounds per hour, nor more than **0.21** tons per year.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.039** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.18** pounds per hour, nor more than **0.029** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.18** pounds per hour, nor more than **0.029** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.18** pounds per hour, nor more than **0.029** tons per year.
 - (4) The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **0.35** pounds per hour, nor more than **0.059** tons per year.
 - (5) The discharge of **VOC** (volatile organic compound) to the atmosphere shall not exceed **3.66** pounds per hour, nor more than **0.61** tons per year.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

H. Emission Units PF1.038 through PF1.040 (continued)

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*) (continued)
 - c. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.040** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.16** pounds per hour, nor more than **0.026** tons per year.
 - (4) The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **0.40** pounds per hour, nor more than **0.067** tons per year.
 - (5) The discharge of **VOC** (volatile organic compound) to the atmosphere shall not exceed **1.25** pounds per hour, nor more than **0.21** tons per year.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

 - a. Monitor and record the throughput for **PF1.038 through PF1.040, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.038 through PF1.040, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. The Permittee, upon issuance of this operating permit, shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative. (40 CFR 60.7(b))
5. Federal Requirements (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
New Source Performance Standards (NSPS) – 40 CFR Part 60 Subpart I – Standards of Performance for Hot Mix Asphalt Facilities (40 CFR Part 60.90)
 - a. On and after the date on which the performance test required to be conducted for **PF1.038 through PF1.040, each**, is completed, the Permittee subject to the provisions of this subpart shall not discharge or cause the discharge into the atmosphere gasses which:
 - (1) Exhibit **20** percent opacity, or greater.
 - b. The opacity standard set forth in this part shall apply at all times except during periods of startup, shutdown, and malfunction (40 CFR Part 60.11(c)).
 - c. At all times, including periods of startup, shutdown, and malfunction, Permittee shall, to the extent practicable, maintain and operate **PF1.038 through PF1.040, each**, including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR Part 60.11(d))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

I. Emission Unit S2.002

System 09 – Asphalt Plant – Drum Dryer		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.002	Drum Dryer (Diesel-Fired)	4,489,885	497,022

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.002** shall be controlled by a **baghouse**.
 - b. Descriptive Stack Parameters
 Stack Height: 41.5 feet
 Stack Diameter: 4.53 feet
 Stack Temperature: 300 °F
 Exhaust Flow: 40,228 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.002** shall not exceed **300.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **100,000.0** tons per year.
 - b. **S2.002** may consume only **diesel**.
 - c. The maximum allowable fuel consumption rate for **S2.002** shall not exceed **500.0** gallons of **diesel** per any one-hour period.
 - d. Hours
 - (1) **S2.002** may operate a total of **12** hours per day.
 - (2) **S2.002** may operate a total of **4,380** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.002** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **9.90** pounds per hour, nor more than **1.65** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **6.90** pounds per hour, nor more than **1.15** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **6.90** pounds per hour, nor more than **1.15** tons per year.
 - d. The discharge of **NO_x** (oxides of nitrogen) to the atmosphere shall not exceed **16.5** pounds per hour, nor more than **2.75** tons per year.
 - e. The discharge of **SO₂** (sulfur dioxide) to the atmosphere shall not exceed **3.30** pounds per hour, nor more than **0.55** tons per year.
 - f. The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **39.0** pounds per hour, nor more than **6.50** tons per year.
 - g. The discharge of **VOC** (volatile organic compound) to the atmosphere shall not exceed **9.60** pounds per hour, nor more than **1.60** tons per year.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

I. Emission Unit S2.002 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **S2.002** on a daily basis.
 - b. Monitor and record the hours of operation for **S2.002** on a daily basis.
 - c. Monitor and record the consumption rate of **diesel** on a daily basis for **S2.002** (in **gallons**) by multiplying the maximum hourly fuel consumption rate as stated in **I.2.b** of this section and the total daily hours of operation.
 - d. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - e. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - f. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - g. Conduct and record an observation of visible emissions (excluding water vapor) on the baghouse controlling **S2.002** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
 - h. Inspect the baghouse installed on **S2.002** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.
 - i. The Permittee, upon issuance of this operating permit, shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative. (40 CFR 60.7(b))

5. Performance and Compliance Testing (NAC 445B.346(2), NAC 445B.252(1)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall conduct renewal performance testing at least 90 days prior to the expiration of this operating permit, but no earlier than 365 days from the date of expiration of this operating permit, and every 5 years thereafter, in accordance with the following:
 - a. All opacity compliance demonstrations and/ performance tests must comply with the advance notification, protocol review, operational conditions, reporting, and other requirements of Section I.H. Testing and Sampling (NAC 445B.252) of this operating permit. Material sampling must be conducted in accordance with protocols approved by the Director. All performance test results shall be based on the arithmetic average of three valid runs (NAC 445B.252(5)).
 - b. Testing shall be conducted on the exhaust stack (post controls).
 - c. Method 5 in Appendix A of 40 CFR Part 60 shall be used to determine PM emissions. The sample volume for each test run shall be at least 1.7 dscm (60 dscf). Test runs must be conducted for up to two hours in an effort to collect this minimum sample.
 - d. Method 201A and Method 202 in Appendix M of 40 CFR Part 51 shall be used to determine PM₁₀ and PM_{2.5} emissions. The sample time and sample volume collected for each test run shall be sufficient to collect enough mass to weigh accurately.
 - e. The Method 201A and 202 test required in this section may be replaced by a Method 5 in Appendix A of 40 CFR Part 60 and Method 202 in Appendix M of 40 CFR Part 51 test. All particulate captured in the Method 5 and Method 202 test performed under this provision shall be considered PM_{2.5} for determination of compliance.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

I. Emission Unit S2.002 (continued)

5. Performance and Compliance Testing (NAC 445B.346(2), NAC 445B.252(1)) (*Federally Enforceable SIP Requirement*) (continued)

The Permittee, upon issuance of this operating permit, shall conduct renewal performance testing at least 90 days prior to the expiration of this operating permit, but no earlier than 365 days from the date of expiration of this operating permit, and every 5 years thereafter, in accordance with the following: (continued)

- f. Method 6C in Appendix A of 40 CFR Part 60 shall be used to determine the sulfur dioxide concentration. Each test will be run for a minimum of one hour.
- g. Method 7E in Appendix A of 40 CFR Part 60 shall be used to determine the nitrogen oxides concentration. Each test will be run for a minimum of one hour.
- h. Method 10 in Appendix A of 40 CFR Part 60 shall be used to determine the carbon monoxide concentration. Each test will be run for a minimum of one hour.
- i. Method 25A in Appendix A of 40 CFR Part 60 shall be used to determine the volatile organic compound concentration. Method 18 in Appendix A of 40 CFR Part 60 or Method 320 in Appendix A of CFR Part 63 may be used in conjunction with Method 25A to break out the organic compounds that are not considered VOC's by definition per 40 CFR 51.100(s). Each Method 25A test will be run for a minimum of one hour.
- j. Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.

6. Federal Requirements (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
New Source Performance Standards (NSPS) – 40 CFR Part 60 Subpart I – Standards of Performance for Hot Mix Asphalt Facilities (40 CFR Part 60.90)

- a. On and after the date on which the performance test required to be conducted for **S2.002** is completed, the Permittee subject to the provisions of this subpart shall not discharge or cause the discharge into the atmosphere gasses which:
 - (1) Contain particulate matter in excess of **90 mg/dscm** (0.04 gr/dscf). (40 CFR Part 60.92(a)(1))
 - (2) Exhibit **20** percent opacity, or greater.
- b. The opacity standard set forth in this part shall apply at all times except during periods of startup, shutdown, and malfunction (40 CFR Part 60.11(c)).
- c. At all times, including periods of startup, shutdown, and malfunction, Permittee shall, to the extent practicable, maintain and operate **S2.002** including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR Part 60.11(d))



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

J. Emission Units PF1.041 through PF1.047

System 10 – Wash Plant – Conveyor Transfers		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.041	Loader Transfer to Bin Feeder	4,489,987	496,741
PF1.042	Bin Feeder Transfer to Conveyor C-29	4,489,987	496,741
PF1.043	Sand Screw SS-1 Transfer to Radial Stacker C-33	4,490,012	496,745
PF1.044	Radial Stacker C-33 Transfer to Stockpile 7	4,490,031	496,727
PF1.045	Conveyor C-30 Transfer to Stockpile 8	4,489,998	496,765
PF1.046	Conveyor C-31 Transfer to Stockpile 9	4,490,010	496,770
PF1.047	Conveyor C-32 Transfer to Stockpile 10	4,490,021	496,768

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.041 and PF1.042, each, have no add-on controls.
Emissions from **PF1.043 through PF1.047, each**, shall be controlled by **fully saturated material**.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.041 through PF1.047, each**, shall not exceed **180.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **80,000.0** tons per year.
 - b. Hours
 - (1) **PF1.041 through PF1.047, each**, may operate a total of **16** hours per day.
 - (2) **PF1.041 through PF1.047, each**, may operate a total of **5,840** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.041 and PF1.042, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.54** pounds per hour, nor more than **0.12** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.20** pounds per hour, nor more than **0.044** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.030** pounds per hour, nor more than **0.0067** tons per year.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.043 through PF1.047, each**, the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - c. The opacity from **PF1.041 and PF1.042, each**, shall not equal or exceed **20** percent.
 - d. The opacity from **PF1.043 through PF1.047, each**, shall not exceed **0** percent.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

J. Emission Units PF1.041 through PF1.047 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **PF1.041 through PF1.047, each**, on a daily basis.
- b. Monitor and record the hours of operation for **PF1.041 through PF1.047, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
- f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.043 through PF1.047, each**, on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

K. Emission Unit PF1.048

System 11 – Wash Plant – Wash Screen		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.048	Wash Screen S-4 and Associated Transfers (In: Conveyor C-29; Out: Conveyor C-30, Conveyor C-31, Conveyor C-32, and Sand Screw SS-1)	4,490,010	496,749

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
Emissions from **PF1.048** shall be controlled by **fully saturated material**.
2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.048** shall not exceed **180.0** tons of **aggregate** per any one-hour period averaged over a daily basis, nor more than **80,000.0** tons per year.
 - b. Hours
 - (1) **PF1.048** may operate a total of **16** hours per day.
 - (2) **PF1.048** may operate a total of **5,840** hours per year.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.048** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.00** pounds per hour, nor more than **0.00** tons per year.
 - d. The opacity from **PF1.048** shall not exceed **0** percent.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.048** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.048** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.048** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.

*****End of Specific Operating Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section VI. Emission Caps

A. Not Applicable

*****End of Emission Caps*****

DRAFT



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section VII. Surface Area Disturbance Conditions

The surface area disturbance for **305 Pit** is **40.0** acres.

A. Fugitive Dust (NAC 445B.22037) (*Federally Enforceable SIP Requirement*)

1. No person may cause or permit the handling, transporting or storing of any material in a manner which allows or may allow controllable particulate matter to become airborne.
2. Except as otherwise provided in subsection 4, no person may cause or permit the construction, repair, demolition, or use of unpaved or untreated areas without first putting into effect an ongoing program using the best practical methods to prevent particulate matter from becoming airborne. As used in this subsection, “best practical methods” includes, but is not limited to, paving, chemical stabilization, watering, phased construction and revegetation.
3. Except as otherwise provided in subsection 4, no person may disturb or cover 5 acres or more of land or its topsoil until he has obtained an operating permit for surface area disturbance to clear, excavate, or level the land or to deposit any foreign material to fill or cover the land.
4. The provisions of subsections 2 and 3 do not apply to:
 - a. Agricultural activities occurring on agricultural land; or
 - b. Surface disturbances authorized by a permit issued pursuant to NRS 519A.180 which occur on land which is not less than 5 acres or more than 20 acres.

*****End of Surface Area Disturbance Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section VIII. Schedules of Compliance

A. Not Applicable

*****End of Schedule of Compliance*****

DRAFT



Bureau of Air Pollution Control

Facility ID No. A0642

Permit No. AP1442-4633

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: H.E. HUNEWILL CONSTRUCTION CO. INC. – 305 PIT (AS PERMITTEE)

Section IX. Amendments

Date, Air Case 11908

- New Class II

This permit:

1. **Is non-transferable.** (NAC 445B.287.3) (*Federally Enforceable SIP Requirement*)
2. **Will be posted conspicuously at or near the stationary source.** (NAC 445B.318.5) (*Federally Enforceable SIP Requirement*)
3. **Will expire and be subject to renewal five (5) years from:** _____ **Date** _____ .
(NAC 445B.315) (*Federally Enforceable SIP Requirement*)
4. **A completed application for renewal of an operating permit must be submitted to the director on the form provided by him with the appropriate fee at least 70 calendar days before the expiration date of this operating permit.** (NAC 445B.3473.2) (*Federally Enforceable SIP Requirement*)
5. **Any person aggrieved by a final decision of the Department may, not later than 10 days after notice of the action of the Department, appeal the decision by filing a request for a hearing before the Commission on a form 3* with the State Environmental Commission, 901 South Stewart Street, Suite 4001, Carson City, Nevada 89701-5249.**
**(See adopting agency for form.) (NAC 445B.890) (State Only Requirement)*

THIS PERMIT EXPIRES ON: _____ **Date** _____

Signature: _____

Issued by: **XXXXXXXXXX**
Supervisor, Permitting Branch
Bureau of Air Pollution Control

Phone: _____ (775) 687- **XXXX** **Date:** _____ **Date** _____

Class II Insignificant Activities List

Appended to Permit #AP1442-4633

Emission Unit #	Emission Unit Description
IA1.001	Diesel Fuel Tank 1
IA1.002	Diesel Fuel Tank 2
IA1.003	Asphalt Oil Tank