



Bureau of Air Pollution Control

901 SOUTH STEWART STREET SUITE 4001

CARSON CITY, NEVADA 89701-5249

p: 775-687-9349 • ndep.nv.gov/air

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT AND SONS, LLC. (HEREINAFTER REFERRED TO AS PERMITTEE)

Mailing Address: P.O. BOX 5009, FALLON, NV 89407

Physical Address: 2120 SOUTH ALLEN ROAD, FALLON, NV 89406

Driving Directions: FROM THE INTERSECTION OF US-50 (WEST WILLIAMS AVENUE) AND US-95 (SOUTH TAYLOR STREET) IN FALLON, NV, HEAD SOUTH ON US-95 FOR 1 MILE TO NV-117 (SHECKLER ROAD) AND TURN RIGHT. FOLLOW FOR 1 MILE TO SOUTH ALLEN ROAD AND TURN LEFT. THE ENTRANCE TO THE FACILITY WILL BE ON THE RIGHT.

General Facility Location: SECTION 2, T 18 N, R 28 E, MDB&M
HA 101 – CARSON DESERT / CHURCHILL COUNTY
NORTH 4,368,957 M, EAST 344,925 M, UTM ZONE 11, NAD 83

Emission Unit List:

A. System 1 - Sand Loading (South)

- PF1.001 Loader transfer of Concrete Sand to Bin #1
- PF1.002 Bin #1 transfer of Concrete Sand to Conveyor #1
- PF1.003 Conveyor #1 transfer of Concrete Sand to Bin #2 and Bin #3

B. System 2 - Aggregate Loading (South)

- PF1.004 Loader transfer of Aggregate Concrete Rock to Bin #1
- PF1.005 Bin #1 transfer of Aggregate Concrete Rock to Conveyor #1
- PF1.006 Conveyor #1 transfer of Aggregate Concrete Rock to Bin #4 and Bin #5

C. System 3 - Sand and Aggregate Loading (South)

- PF1.007 Bin #2, Bin #3, Bin #4 and Bin #5 transfer to Bin #6
- PF1.008 Bin #6 transfer to Conveyor #2

D. System 4 - Cement Silo (South)

- S2.001 Pneumatic loading of Cement from Truck to Arrowhead Silo (B-7)
- S2.002 Arrowhead Silo (B-7) discharge to Weigh Hopper (B-8)

E. System 5 - Pozzolan Silo (South)

- S2.003 Pneumatic loading of Pozzolan from Truck to Arrowhead Silo (B-7)
- S2.004 Arrowhead Silo (B-7) discharge to Weigh Hopper (B-8)

F. System 6 - Truck Loading (South)

- S2.005 Conveyor #2 transfer of Sand and Aggregate into Truck
- S2.006 Weigh Hopper (B-8) transfer of Cement and Pozzolan into Truck

G. System 7 - Water Heater (South)

- S2.007 4.57 MMBtu/hr Propane Fired Direct Contact Water Heater

H. System 8 - Sand Screen Loading

- PF1.009 Front Loader transfer to Feed Hopper
- PF1.010 Feed Hopper transfer to Conveyor #4 Feed Belt

I. System 9 - Sand Screen

- PF1.011 Sand Screen and Associated Transfers (In: Conveyor C-4, Out: Conveyor C-5 and Oversize Stockpile)



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Emission Unit List: (continued)

J. System 10 – Sand Screen Stockpile Discharge

PF1.012 Conveyor C-5 transfer to Sand Stockpile

K. System 11 - Sand Loading (North)

PF1.013 Front Loader transfer to Sand Feed Bin

PF1.014 Sand Feed Bin transfer to Sand Conveyor C-2

PF1.015 Sand Conveyor C-2 transfer to Weigh Hopper

L. System 12 - Aggregate Loading (North)

PF1.016 Loader transfer to Rock Feed Bin

PF1.017 Rock Feed Bin transfer to Rock Conveyor C-3

PF1.018 Rock Conveyor C-3 transfer to Weigh Hopper

M. System 13 - Weigh Hopper (North)

PF1.019 Weigh Hopper transfer to Charge Conveyor Belt C-1

N. System 14 - Charge Conveyor Discharge (North)

PF1.020 Charge Belt Conveyor C-1 Discharge to Truck

O. System 15 - Cement Silo (North)

S2.008 Cement Silo Loading

PF1.021 Cement Silo Discharge to Truck

P. System 16 - Diesel Generator (North)

~~S2.009 50 Hp Diesel Generator, Deutz Engine, Serial #: 790502, Year: 1980~~ (replaced by S2.010)

S2.010 165 HP MQ Power Diesel Generator for Sand Screen Plant (John Deere engine, mdl# 6068TF275, mfd 2005, EPA Tier II)

******End of Emission Unit List******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions

- A. Prohibited acts; penalty; establishment of violation; request for prosecution (NRS 445B.470) (*State Only Requirement*)
1. A person shall not knowingly:
 - a. Violate any applicable provision, the terms or conditions of any permit or any provision for the filing of information;
 - b. Fail to pay any fee;
 - c. Falsify any material statement, representation or certification in any notice or report; or
 - d. Render inaccurate any monitoring device or method, required pursuant to the provisions of NRS 445B.100 to 445B.450, inclusive, or 445B.470 to 445B.640, inclusive, or any regulation adopted pursuant to those provisions.
 2. Any person who violates any provision of subsection 1 shall be punished by a fine of not more than \$10,000 for each day of the violation.
 3. The burden of proof and degree of knowledge required to establish a violation of subsection 1 are the same as those required by 42 U.S.C. § 7413(c), as that section existed on October 1, 1993.
 4. If, in the judgment of the Director of the Department or the Director's designee, any person is engaged in any act or practice which constitutes a criminal offense pursuant to NRS 445B.100 to 445B.640, inclusive, the Director of the Department or the designee may request that the Attorney General or the district attorney of the county in which the criminal offense is alleged to have occurred institute by indictment or information a criminal prosecution of the person.
 5. If, in the judgment of the control officer of a local air pollution control board, any person is engaged in such an act or practice, the control officer may request that the district attorney of the county in which the criminal offense is alleged to have occurred institute by indictment or information a criminal prosecution of the person.
- B. Visible emissions: Maximum opacity; determination and monitoring of opacity (NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
1. Except as otherwise provided in this section and NAC 445B.2202, no owner or operator may cause or permit the discharge into the atmosphere from any emission unit which is of an opacity equal to or greater than 20 percent. Opacity must be determined by one of the following methods:
 - a. If opacity is determined by a visual measurement, it must be determined as set forth in Reference Method 9 in Appendix A of 40 CFR Part 60.
 - b. If a source uses a continuous monitoring system for the measurement of opacity, the data must be reduced to 6-minute averages as set forth in 40 CFR 60.13(h).
 2. The provisions of this section and NAC 445B.2202 do not apply to that part of the opacity that consists of uncombined water. The burden of proof to establish the application of this exemption is upon the person seeking to come within the exemption.
 3. If the provisions of 40 CFR Part 60, Subpart D or Da apply to an emission unit, the emission unit must be allowed one 6-minute period per hour of not more than 27 percent opacity as set forth in 40 CFR 60.42(a)(2) and 40 CFR 60.42a(b).
 4. The continuous monitoring system for monitoring opacity at a facility must be operated and maintained by the owner or operator specified in the permit for the facility in accordance with NAC 445B.256 to 445B.267, inclusive.
- C. Visible emissions: Exceptions for stationary sources (NAC 445B.2202) (*Federally Enforceable SIP Requirement*)
- The provisions of NAC 445B.22017 do not apply to:
1. Smoke from the open burning described in NAC 445B.22067;
 2. Smoke discharged in the course of training air pollution control inspectors to observe visible emissions, if the facility has written approval of the Commission;
 3. Emissions from an incinerator as set forth in NAC 445B.2207; or
 4. Emissions of stationary diesel-powered engines during warm-up for not longer than 15 minutes to achieve operating temperatures.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions (continued)

D. Odors (NAC 445B.22087) (*State Only Requirement*)

1. No person may discharge or cause to be discharged, from any stationary source, any material or regulated air pollutant which is or tends to be offensive to the senses, injurious or detrimental to health and safety, or which in any way interferes with or prevents the comfortable enjoyment of life or property.
2. The Director shall investigate an odor when 30 percent or more of a sample of the people exposed to it believe it to be objectionable in usual places of occupancy. The sample must be at least 20 people or 75 percent of those exposed if fewer than 20 people are exposed.
3. The Director shall deem the odor to be a violation if he or she is able to make two odor measurements within a period of 1 hour. These measurements must be separated by at least 15 minutes. An odor measurement consists of a detectable odor after the odorous air has been diluted with eight or more volumes of odor-free air.

E. Prohibited Conduct: Concealment of Emissions (NAC 445B.225) (*Federally Enforceable SIP Requirement*)

No person may install, construct or use any device which conceals any emission without reducing the total release of regulated air pollutants to the atmosphere.

F. Prohibited conduct: Operation of source without required equipment; removal or modification of required equipment; modification of required procedure (NAC 445B.227) (*Federally Enforceable SIP Requirement*)

Except as otherwise provided in NAC 445B.001 to 445B.390, inclusive, no person may:

1. Operate a stationary source of air pollution unless the control equipment for air pollution which is required by applicable requirements or conditions of this Operating Permit is installed and operating.
2. Disconnect, alter, modify or remove any of the control equipment for air pollution or modify any procedure required by an applicable requirement or condition of the permit.

G. Excess Emissions (NAC 445B.232) (*State Only Requirement*)

1. Scheduled maintenance or testing or scheduled repairs which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.390, inclusive, must be approved in advance by the Director and performed during a time designated by the Director as being favorable for atmospheric ventilation.
2. Each owner or operator shall notify the Director of the proposed time and expected duration at least 30 days before any scheduled maintenance or testing which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.390, inclusive. The scheduled maintenance or testing must not be conducted unless the scheduled maintenance or testing is approved pursuant to subsection 1.
3. Each owner or operator shall notify the Director of the proposed time and expected duration at least 24 hours before any scheduled repairs which may result in excess emissions of regulated air pollutants prohibited by NAC 445B.001 to 445B.390, inclusive. The scheduled repairs must not be conducted unless the scheduled repairs are approved pursuant to subsection 1.
4. Each owner or operator shall notify the Director of any excess emissions within 24 hours after any malfunction or upset of the process equipment or equipment for controlling pollution or during start-up or shutdown of that equipment.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions (continued)

G. Excess Emissions (NAC 445B.232) (*State Only Requirement*) (continued)

5. Each owner or operator shall provide the Director, within 15 days after any malfunction, upset, start-up, shutdown or human error which results in excess emissions, sufficient information to enable the Director to determine the seriousness of the excess emissions. The information must include at least the following:
 - a. The identity of the stack or other point of emission, or both, where the excess emissions occurred.
 - b. The estimated magnitude of the excess emissions expressed in opacity or in the units of the applicable limitation on emission and the operating data and methods used in estimating the magnitude of the excess emissions.
 - c. The time and duration of the excess emissions.
 - d. The identity of the equipment causing the excess emissions.
 - e. If the excess emissions were the result of a malfunction, the steps taken to remedy the malfunction and the steps taken or planned to prevent the recurrence of the malfunction.
 - f. The steps taken to limit the excess emissions.
 - g. Documentation that the equipment for controlling air pollution, process equipment or processes were at all times maintained and operated, to a maximum extent practicable, in a manner consistent with good practice for minimizing emissions.
6. Each owner or operator shall ensure that any notification or related information submitted to the Director pursuant to this section is provided in a format specified by the Director.

H. Testing and Sampling (NAC 445B.252) (*Federally Enforceable SIP Requirement*)

1. To determine compliance with NAC 445B.001 to 445B.390, inclusive, before the approval or the continuance of an operating permit or similar class of permits, the Director may either conduct or order the owner of any stationary source to conduct or have conducted such testing and sampling as the Director determines necessary. Testing and sampling or either of them must be conducted and the results submitted to the Director within 60 days after achieving the maximum rate of production at which the affected facility will be operated, but not later than 180 days after initial start-up of the facility and at such other times as may be required by the Director.
2. Tests of performance must be conducted and data reduced in accordance with the methods and procedures of the test contained in each applicable subsection of this section unless the Director:
 - a. Specifies or approves, in specific cases, the use of a method of reference with minor changes in methodology;
 - b. Approves the use of an equivalent method;
 - c. Approves the use of an alternative method, the results of which the Director has determined to be adequate for indicating whether a specific stationary source is in compliance; or
 - d. Waives the requirement for tests of performance because the owner or operator of a stationary source has demonstrated by other means to the Director's satisfaction that the affected facility is in compliance with the standard.
3. Tests of performance must be conducted under such conditions as the Director specifies to the operator of the plant based on representative performance of the affected facility. The owner or operator shall make available to the Director such records as may be necessary to determine the conditions of the performance test. Operations during periods of startup, shutdown and malfunction must not constitute representative conditions of a performance test unless otherwise specified in the applicable standard.
4. The owner or operator of an affected facility shall give notice to the Director 30 days before the test of performance to allow the Director to have an observer present. A written testing procedure for the test of performance must be submitted to the Director at least 30 days before the test of performance to allow the Director to review the proposed testing procedures.
5. Each test of performance must consist of at least three separate runs using the applicable method for that test. Each run must be conducted for the time and under the conditions specified in the applicable standard. For the purpose of determining compliance with an applicable standard, the arithmetic means of results of the runs apply. In the event of forced shutdown, failure of an irreplaceable portion of the sampling train, extreme meteorological conditions or other circumstances with less than three valid samples being obtained, compliance may be determined using the arithmetic mean of the results of the other two runs upon the Director's approval.
6. All testing and sampling will be performed in accordance with recognized methods and as specified by the Director.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions (continued)

H. Testing and Sampling (NAC 445B.252) (*Federally Enforceable SIP Requirement*) (continued)

7. The cost of all testing and sampling and the cost of all sampling holes, scaffolding, electric power and other pertinent allied facilities as may be required and specified in writing by the Director must be provided and paid for by the owner of the stationary source.
8. All information and analytical results of testing and sampling must be certified as to their truth and accuracy and as to their compliance with all provisions of these regulations, and copies of these results must be provided to the Director no later than 60 days after the testing or sampling, or both.
9. Notwithstanding the provisions of subsection 2, the Director shall not approve an alternative method or equivalent method to determine compliance with a standard or emission limitation contained in Part 60, 61 or 63 of Title 40 of the Code of Federal Regulations for:
 - a. An emission unit that is subject to a testing requirement pursuant to Part 60, 61 or 63 of Title 40 of the Code of Federal Regulations; or
 - b. An affected source.

I. Permit Revision (NAC 445B.287(1)(b)) (*Federally Enforceable SIP Requirement*)

If a stationary source is a Class II source, a revision of the operating permit or the permit to construct is required pursuant to the requirements of NAC 445B.3465 before the stationary source may be modified.

J. Violations: Acts constituting; notice (NAC 445B.275) (*Federally Enforceable SIP Requirement*)

1. Failure to comply with any requirement of NAC 445B.001 to 445B.390, inclusive, any applicable requirement or any condition of an operating permit constitutes a violation. As required by NRS 445B.450, the Director shall issue a written notice of an alleged violation to any owner or operator for any violation, including, but not limited to:
 - a. Failure to apply for and obtain an operating permit;
 - b. Failure to construct a stationary source in accordance with the application for an operating permit as approved by the Director;
 - c. Failure to construct or operate a stationary source in accordance with any condition of an operating permit;
 - d. Commencing construction or modification of a stationary source without applying for and receiving an operating permit or a modification of an operating permit as required by NAC 445B.001 to 445B.3477, inclusive, or a mercury operating permit to construct as required by NAC 445B.3611 to 445B.3689, inclusive;
 - e. Failure to comply with any requirement for recordkeeping, monitoring, reporting or compliance certification contained in an operating permit; or
 - f. Failure to pay fees as required by NAC 445B.327 or 445B.3689.
2. The written notice must specify the provision of NAC 445B.001 to 445B.390, inclusive, the condition of the operating permit or the applicable requirement that is being violated.
3. Written notice shall be deemed to have been served if delivered to the person to whom addressed or if sent by registered or certified mail to the last known address of the person.

K. Operating permits: Imposition of more stringent standards for emissions (NAC 445B.305)

(*Federally Enforceable SIP Requirement*)

1. The Director may impose standards for emissions on a proposed stationary source that are more stringent than those found in NAC 445B.001 to 445B.390, inclusive, as a condition of approving an operating permit for the proposed stationary source.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions (continued)

L. Contents of operating permits: Exception for operating permits to construct; required conditions (NAC 445B.315)
(*Federally Enforceable SIP Requirement*)

1. Notwithstanding any provision of this section to the contrary, the provisions of this section do not apply to operating permits to construct.
2. The Director shall cite the legal authority for each condition contained in an operating permit.
3. An operating permit must contain the following conditions:
 - a. The term of the operating permit is 5 years.
 - b. The holder of the operating permit shall retain records of all required monitoring data and supporting information for 5 years after the date of the sample collection, measurement, report or analysis. Supporting information includes all records regarding calibration and maintenance of the monitoring equipment and all original strip-chart recordings for continuous monitoring instrumentation.
 - c. Each of the conditions and requirements of the operating permit is severable, and if any are held invalid, the remaining conditions and requirements continue in effect.
 - d. The holder of the operating permit shall comply with all conditions of the operating permit. Any noncompliance constitutes a violation and is a ground for:
 - (1) An action for noncompliance;
 - (2) Revising, revoking, reopening and revising, or terminating the operating permit by the Director; or
 - (3) Denial of an application for a renewal of the operating permit by the Director.
 - e. The need to halt or reduce activity to maintain compliance with the conditions of the operating permit is not a defense to noncompliance with any condition of the operating permit.
 - f. The Director may revise, revoke and reissue, reopen and revise, or terminate the operating permit for cause.
 - g. The operating permit does not convey any property rights or any exclusive privilege.
 - h. The holder of the operating permit shall provide the Director, in writing and within a reasonable time, with any information that the Director requests to determine whether cause exists for revising, revoking and reissuing, reopening and revising, or terminating the operating permit, or to determine compliance with the conditions of the operating permit.
 - i. The holder of the operating permit shall pay fees to the Director in accordance with the provisions set forth in NAC 445B.327 and 445B.331.
 - j. The holder of the operating permit shall allow the Director or any authorized representative, upon presentation of credentials, to:
 - (1) Enter upon the premises of the holder of the operating permit where:
 - (a) The stationary source is located;
 - (b) Activity related to emissions is conducted; or
 - (c) Records are kept pursuant to the conditions of the operating permit;
 - (2) Have access to and copy, during normal business hours, any records that are kept pursuant to the conditions of the operating permit;
 - (3) Inspect, at reasonable times, any facilities, practices, operations or equipment, including any equipment for monitoring or controlling air pollution, that are regulated or required pursuant to the operating permit; and
 - (4) Sample or monitor, at reasonable times, substances or parameters to determine compliance with the conditions of the operating permit or applicable requirements.
 - k. A responsible official of the stationary source shall certify that, based on information and belief formed after a reasonable inquiry, the statements made in any document required to be submitted by any condition of the operating permit are true, accurate and complete.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section I. General Provisions (continued)

M. Operating permits: Revocation and reissuance (NAC 445B.3265) (*State Only Requirement*)

1. An operating permit may be revoked if the control equipment is not operating.
2. An operating permit may be revoked by the Director upon determining that there has been a violation of NAC 445B.001 to 445B.390, inclusive, or the provisions of 40 CFR 52.21, or 40 CFR Part 60 or 61, Prevention of Significant Deterioration, New Source Performance Standards, and National Emission Standards for Hazardous Air Pollutants, adopted by reference in NAC 445B.221.
3. The revocation is effective 10 days after the service of a written notice, unless a hearing is requested.
4. To reissue a revoked operating permit, the holder of the revoked permit must file a new application with the Director, accompanied by the fee for an initial operating permit as specified in NAC 445B.327. An environmental review of the stationary source must be conducted as though construction had not yet commenced.

N. Required contents of permit (NAC 445B.346) (*Federally Enforceable SIP Requirement*)

In addition to the conditions set forth in NAC 445B.315, Class II operating permits must contain, as applicable:

1. Emission limitations and standards, including those operational requirements and limitations that ensure compliance with the conditions of the operating permit.
2. All requirements for monitoring, testing and reporting that apply to the stationary source.
3. A requirement that the owner or operator of the stationary source promptly report any deviations from any requirements of the operating permit.
4. The terms and conditions for any reasonably anticipated alternative operating scenarios identified by the owner or operator of the stationary source in his or her application and approved by the Director. Such terms and conditions must require the owner or operator to keep a contemporaneous log of changes from one alternative operating scenario to another.
5. A schedule of compliance for stationary sources that are not in compliance with any applicable requirement or NAC 445B.001 to 445B.390, inclusive:
 - a. Semiannual progress reports and a schedule of dates for achieving milestones;
 - b. Prior notice of and explanations for missed deadlines; and
 - c. Any preventive or corrective measures taken.

*****End of General Provisions*****



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section II. General Monitoring, Recordkeeping, and Reporting Conditions

A. Records Retention (NAC 445B.315(3)(b)) (*Federally Enforceable SIP Requirement*)

The holder of the operating permit shall retain records of all required monitoring data and supporting information for 5 years after the date of the sample collection, measurement, report or analysis. Supporting information includes all records regarding calibration and maintenance of the monitoring equipment and all original strip-chart recordings for continuous monitoring instrumentation.

B. Deviations (NAC 445B.346(3)) (*Federally Enforceable SIP Requirement*)

Under the authority of NAC 445B.346(3), and in addition to the conditions set forth in NAC 445B.315, the owner or operator of the stationary source shall promptly report to the Director any deviations from the requirements of the operating permit. The report to the Director shall include the probable cause of all deviations and any action taken to correct the deviations. For the operating permit, prompt is defined as submittal of a report within 15 days of the deviation. This definition does not alter any reporting requirements as established for reporting of excess emissions as required under NAC 445B.232 as reproduced in **Section I.G.**

E-mail notifications to: aircompliance@ndep.nv.gov

C. Yearly Reports (NAC 445B.315(3)(h), NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

Under the authority of NAC 445B.315(3)(h) and NAC 445B.346(2) the Permittee will submit yearly reports including, but not limited to, throughput, production, fuel consumption, hours of operation, emissions and supporting documentation to support the calculation of annual emissions. These reports and supporting documentation (if applicable) will be submitted via the State and Local Emissions Inventory System (SLEIS) maintained by the Bureau of Air Quality Planning for all emission units/systems specified. The completed report must be submitted to the Bureau of Air Quality Planning no later than March 1 annually for the preceding calendar year.

*****End of General Monitoring, Recordkeeping, and Reporting Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section III. General Construction Conditions

A. Notification (NAC 445B.250; NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

Under the authority of NAC 445B.250 and NAC 445B.346; the Director shall be notified in writing of the following for **S2.010**:

1. The date construction (or reconstruction as defined under NAC 445B.247) of the affected facility is commenced, postmarked no later than 30 days after such date. This requirement shall not apply in the case of mass-produced facilities which are purchased in completed form.
2. The anticipated date of initial startup of an affected facility, postmarked no more than 60 days and no less than 30 days prior to such date.
3. The actual date of initial startup of the affected facility, postmarked within 15 days after such date.
4. The date upon which demonstration of the continuous monitoring system performance commences in accordance with NAC 445B.256 to 445B.267, inclusive. Notification must be postmarked not less than 30 days before such date.

******End of General Construction Conditions******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section IV. Specific Construction Requirements

A. Initial Opacity Compliance Demonstration and Initial Performance Tests (NAC 445B.22017, NAC 445B.252, NAC 445B.346(2))
(Federally Enforceable SIP Requirement)

1. Under the authority of NAC 445B.22017, NAC 445B.252, and NAC 445B.346, the Permittee, upon issuance of this operating permit, shall conduct initial opacity compliance demonstrations and/or initial performance tests within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup. The Permittee shall follow the test methods and procedures referenced in Table IV-1 below:

Table IV-1: Initial Opacity Compliance Demonstration

System*	Emission Unit(s)	Pollutant To Be Tested	Testing Methods/Procedures
System 01 – Sand Loading (South)	PF1.001 PF1.002 PF1.003	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.
System 02 – Aggregate Loading (South)	PF1.004 PF1.005 PF1.006	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.
System 03 – Sand and Aggregate Loading (South)	PF1.007 PF1.008	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.
System 06 – Truck Loading (South)	S2.005	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.
System 16 – Diesel Generator (Sand Screen)	S2.010	Opacity	Method 9 in Appendix A of 40 CFR Part 60 shall be used to determine opacity. Opacity observations shall be conducted concurrently with the applicable performance test. The minimum total time of observations shall be six minutes (24 consecutive observations recorded at 15 second intervals), unless otherwise specified by an applicable subpart.

***Systems 01, 02, 03, 06 required initial opacity testing due to the large increase in hourly throughputs requested in revision application (Air Case 12163)**

2. All initial opacity compliance demonstrations must comply with the advance notification, protocol review, operational conditions, reporting, and other requirements of **Section I.H. Testing and Sampling** (NAC 445B.252) of this operating permit. Material sampling must be conducted in accordance with protocols approved by the Director. All initial performance test results shall be based on the arithmetic average of three valid runs. (NAC 445B.252(5))
3. Testing shall be conducted on the exhaust stack (post controls).



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section IV. Specific Construction Requirements (continued)

- A. Initial Opacity Compliance Demonstration and Initial Performance Tests (NAC 445B.22017, NAC 445B.252, NAC 445B.346(2))
(*Federally Enforceable SIP Requirement*) (continued)
4. Initial opacity compliance demonstrations, as specified in Table IV-1 above, must be conducted under such conditions as the Director specifies to the operator of the plant based on representative performance of the affected facility. The Permittee shall make available to the Director such records as may be necessary to determine the conditions of the initial opacity compliance demonstrations. Operations during periods of startup, shutdown and malfunction must not constitute representative conditions of the initial opacity compliance demonstrations unless otherwise specified in the applicable standard. (NAC 445B.252(3))
 5. The Permittee shall give notice to the Director 30 days before the initial opacity compliance demonstrations to allow the Director to have an observer present. A written testing procedure must be submitted to the Director at least 30 days before the initial opacity compliance demonstrations to allow the Director to review the proposed testing procedures. (NAC 445B.252(4) and 40 CFR Part 60.7(a)(6))
 6. Within 60 days after completing the initial opacity compliance demonstrations contained in Table IV-1 of this section, the Permittee shall furnish the Director a written report of the results. All information and analytical results of testing and sampling must be certified as to the truth and accuracy and as to their compliance with NAC 445B.001 to 445B.3689, inclusive. (NAC 445B.252(8))
 7. Initial opacity compliance demonstrations required under this section that are conducted below the maximum allowable throughput, shall be subject to the Director's review to determine if the throughputs during the initial opacity compliance demonstrations were sufficient to provide adequate compliance demonstration. Should the Director determine that the initial opacity compliance demonstrations do not provide adequate compliance demonstration, the Director may require additional testing.

******End of Specific Construction Requirements******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions

A. Emission Units PF1.001 through PF1.003

System 01 – Sand Loading (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.001	Loader transfer of Concrete Sand to Bin #1	4,368,956	344,892
PF1.002	Bin #1 transfer of Concrete Sand to Conveyor #1	4,368,956	344,892
PF1.003	Conveyor #1 transfer of Concrete Sand to Bin #2 and Bin #3	4,368,954	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.001 through PF1.003, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.001 through PF1.003, each**, shall not exceed **150.0 tons of Concrete Sand** per any one-hour period averaged over a daily basis, nor more than **84,000.0 tons** per year.
 - b. Hours
 - (1) **PF1.001 through PF1.003, each**, may operate a total of **24 hours** per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.001 through PF1.003, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.45 pounds** per hour, nor more than **0.13 tons** per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.17 pounds** per hour, nor more than **0.046 tons** per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.025 pounds** per hour, nor more than **0.0070 tons** per year.
 - d. The opacity from **PF1.001 through PF1.003, each**, shall not equal or exceed **20 percent**.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.001 through PF1.003, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.001 through PF1.003, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

B. Emission Units PF1.004 through PF1.006

System 02 – Aggregate Loading (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.004	Loader transfer of Aggregate Concrete Rock to Bin #1	4,368,956	344,892
PF1.005	Bin #1 transfer of Aggregate Concrete Rock to Conveyor #1	4,368,956	344,892
PF1.006	Conveyor #1 transfer of Aggregate Concrete Rock to Bin #4 and Bin #5	4,368,954	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.004 through PF1.006, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.004 through PF1.006, each**, shall not exceed **200.0** tons of **Aggregate Concrete Rock** per any one-hour period averaged over a daily basis, nor more than **112,000.0** tons per year.
 - b. Hours
 - (1) **PF1.004 through PF1.006, each**, may operate a total of **24** hours per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.004 through PF1.006, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.60** pounds per hour, nor more than **0.17** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.22** pounds per hour, nor more than **0.062** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.033** pounds per hour, nor more than **0.0093** tons per year.
 - d. The opacity from **PF1.004 through PF1.006, each**, shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.004 through PF1.006, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.004 through PF1.006, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

C. Emission Units PF1.007 and PF1.008

System 03 – Sand and Aggregate Loading (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.007	Bin #2, Bin #3, Bin #4 and Bin #5 transfer to Bin #6	4,368,954	344,914
PF1.008	Bin #6 transfer to Conveyor #2	4,368,954	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.007 and PF1.008, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.007 and PF1.008, each**, shall not exceed **350.0 tons of Concrete Sand and Aggregate Concrete Rock** per any one-hour period averaged over a daily basis, nor more than **196,000.0 tons per year**.
 - b. Hours
 - (1) **PF1.007 and PF1.008, each**, may operate a total of **24 hours per day**.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.007 and PF1.008, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **1.05 pounds per hour**, nor more than **0.29 tons per year**.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.39 pounds per hour**, nor more than **0.11 tons per year**.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.058 pounds per hour**, nor more than **0.016 tons per year**.
 - d. The opacity from **PF1.007 and PF1.008, each**, shall not equal or exceed **20 percent**.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.007 and PF1.008, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.007 and PF1.008, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

D. Emission Units S2.001 and S2.002

System 04 – Cement Silo (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.001	Pneumatic loading of Cement from Truck to Arrowhead Silo (B-7)	4,368,970	344,914
S2.002	Arrowhead Silo (B-7) discharge to Weigh Hopper (B-8)	4,368,970	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.001** shall be controlled by **Baghouse A**.
 - b. Emissions from **S2.002** shall be controlled by **Dust Collector C**.
 - c. Descriptive Stack Parameters for S2.001
 Stack Height: 71.0 feet
 Stack Diameter: 1' x 2' feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 6,296.4 dry standard cubic feet per minute (dscfm)
 - d. Descriptive Stack Parameters for S2.002
 Stack Height: 20.0 feet
 Stack Diameter: 3' x 2' feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 5,200.0 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.001 and S2.002, each**, shall not exceed **45.0 tons of Cement** per any one-hour period, nor more than **27,000.0 tons** per year.
 - b. Hours
 (1) **S2.001 and S2.002, each**, may operate a total of **24 hours** per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.001** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.045 pounds** per hour, nor more than **0.013 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.015 pounds** per hour, nor more than **0.0046 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0023 pounds** per hour, nor more than **0.00068 tons** per year.
 - (4) The opacity from **S2.001** shall not equal or exceed **20 percent**.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.002** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.0022 pounds** per hour, nor more than **0.00065 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.0013 pounds** per hour, nor more than **0.00038 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.00019 pounds** per hour, nor more than **0.000057 tons** per year.
 - (4) The opacity from **S2.002** shall not equal or exceed **20 percent**.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

D. Emission Units S2.001 and S2.002 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **S2.001 and S2.002, each**, on a daily basis.
- b. Monitor and record the hours of operation for **S2.001 and S2.002, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Conduct and record an observation of visible emissions (excluding water vapor) on **Baghouse A** controlling **S2.001** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- f. Conduct and record an observation of visible emissions (excluding water vapor) on **Dust Collector C** controlling **S2.002** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- g. Inspect **Baghouse A** installed on **S2.001** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.
- h. Inspect **Dust Collector C** installed on **S2.002** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

E. Emission Units S2.003 and S2.004

System 05 – Pozzolan Silo (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.003	Pneumatic loading of Pozzolan from Truck to Arrowhead Silo (B-7)	4,368,970	344,914
S2.004	Arrowhead Silo (B-7) discharge to Weigh Hopper (B-8)	4,368,970	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.003** shall be controlled by **Baghouse B.**
 - b. Emissions from **S2.004** shall be controlled by **Dust Collector C.**
 - c. Descriptive Stack Parameters for S2.003
 Stack Height: 71.0 feet
 Stack Diameter: 1' x 2' feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 6,296.4 dry standard cubic feet per minute (dscfm)
 - d. Descriptive Stack Parameters for S2.004
 Stack Height: 20.0 feet
 Stack Diameter: 3' x 2' feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 5,200.0 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.003 and S2.004, each**, shall not exceed **25.0 tons of Pozzolan** per any one-hour period, nor more than **7,500.0 tons** per year.
 - b. Hours
 (1) **S2.003 and S2.004, each**, may operate a total of **24 hours** per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.003** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.22 pounds** per hour, nor more than **0.033 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.12 pounds** per hour, nor more than **0.018 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.019 pounds** per hour, nor more than **0.0028 tons** per year.
 - (4) The opacity from **S2.003** shall not equal or exceed **20 percent**.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.004** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.0012 pounds** per hour, nor more than **0.00018 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.00070 pounds** per hour, nor more than **0.00011 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.00011 pounds** per hour, nor more than **0.000016 tons** per year.
 - (4) The opacity from **S2.004** shall not equal or exceed **20 percent**.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

E. Emission Units S2.003 and S2.004 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **S2.003 and S2.004, each**, on a daily basis.
- b. Monitor and record the hours of operation for **S2.003 and S2.004, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Conduct and record an observation of visible emissions (excluding water vapor) on **Baghouse B** controlling **S2.003** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- f. Conduct and record an observation of visible emissions (excluding water vapor) on **Dust Collector C** controlling **S2.004** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- g. Inspect **Baghouse B** installed on **S2.003** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.
- h. Inspect **Dust Collector C** installed on **S2.004** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

F. Emission Units S2.005 and S2.006

System 06 – Truck Loading (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.005	Conveyor #2 transfer of Sand and Aggregate into Truck	4,368,970	344,914
S2.006	Weigh Hopper (B-8) transfer of Cement and Pozzolan into Truck	4,368,970	344,914

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.005 and S2.006, each**, shall be controlled by **Dust Collector C**.
 - b. Descriptive Stack Parameters for S2.005 and S2.006
 Stack Height: 20.0 feet
 Stack Diameter: 3' x 2' feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 5,200.0 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.005** shall not exceed **350.0 tons of Concrete Sand and Aggregate Concrete Rock** per any one-hour period, nor more than **196,000.0 tons** per year.
 - b. The maximum allowable throughput rate for **S2.006** shall not exceed **70.0 tons of Cement and Pozzolan** per any one-hour period, nor more than **42,000.0 tons** per year.
 - c. Hours
 (1) **S2.005 and S2.006, each**, may operate a total of **24 hours** per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.005** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.011 pounds** per hour, nor more than **0.0029 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.0039 pounds** per hour, nor more than **0.0011 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.00058 pounds** per hour, nor more than **0.00016 tons** per year.
 - (4) The opacity from **S2.005** shall not equal or exceed **20 percent**.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.006** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.78 pounds** per hour, nor more than **0.23 tons** per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.22 pounds** per hour, nor more than **0.065 tons** per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.033 pounds** per hour, nor more than **0.0099 tons** per year.
 - (4) The opacity from **S2.006** shall not equal or exceed **20 percent**.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

F. Emission Units S2.005 and S2.006 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **S2.005 and S2.006, each**, on a daily basis.
- b. Monitor and record the hours of operation for **S2.005 and S2.006, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Conduct and record an observation of visible emissions (excluding water vapor) on **Dust Collector C** controlling **S2.005 and S2.006, each**, on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- f. Inspect **Dust Collector C** installed on **S2.005 and S2.006, each**, in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

G. Emission Unit S2.007

System 07 – Water Heater (South)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.007	4.57 MMBtu/hr Propane Fired Direct Contact Water Heater	4,368,943	344,934

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. **S2.007** has no add-on controls.
 - b. Descriptive Stack Parameters
 Stack Height: 25.0 feet
 Stack Diameter: 1.67 feet
 Stack Temperature: 180 °F
 Exhaust Flow: 1,112.6 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. **S2.007** may consume only **Propane**.
 - b. The maximum allowable fuel consumption rate for **S2.007** shall not exceed **49.9 gallons** per any one-hour period.
 - c. Hours
 (1) **S2.007** may operate a total of **24** hours per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.007** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.035** pounds per hour, nor more than **0.15** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.035** pounds per hour, nor more than **0.15** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.035** pounds per hour, nor more than **0.15** tons per year.
 - d. The discharge of **SO₂** (sulfur dioxide) to the atmosphere shall not exceed **0.0050** pounds per hour, nor more than **0.022** tons per year.
 - e. The discharge of **NO_x** (oxides of nitrogen) to the atmosphere shall not exceed **0.65** pounds per hour, nor more than **2.84** tons per year.
 - f. The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **0.37** pounds per hour, nor more than **1.64** tons per year.
 - g. The discharge of **VOCs** (volatile organic compounds) to the atmosphere shall not exceed **0.040** pounds per hour, nor more than **0.17** tons per year.
 - h. The opacity from **S2.007** shall not equal or exceed **20** percent.

4. Monitoring and Recordkeeping (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the hours of operation for **S2.007** on a daily basis.
 - b. Monitor and record the consumption rate of **Propane** on a daily basis for **S2.007** (in **gallons**) by multiplying the maximum hourly fuel consumption rate as stated in **G.2.b** of this section and the total daily hours of operation.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

H. Emission Units PF1.009 and PF1.010

System 08 – Sand Screen Loading		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.009	Front Loader transfer to Feed Hopper	4,369,116	344,814
PF1.010	Feed Hopper transfer to Conveyor #4 Feed Belt	4,369,119	344,828

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.009 and PF1.010, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.009 and PF1.010, each**, shall not exceed **50.0** tons of **Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.009 and PF1.010, each**, may operate a total of **24** hours per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.009 and PF1.010, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.15** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.055** pounds per hour, nor more than **0.040** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0083** pounds per hour, nor more than **0.0061** tons per year.
 - d. The opacity from **PF1.009 and PF1.010, each**, shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.009 and PF1.010, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.009 and PF1.010, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

I. Emission Unit PF1.011

System 09 – Sand Screen		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.011	Sand Screen and Associated Transfers (In: Conveyor C-4, Out: Conveyor C-5 and Oversize Stockpile)	4,369,119	344,828

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
Emissions from **PF1.011** shall be controlled by **water sprays**.
2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.011** shall not exceed **50.0** tons of **Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.011** may operate a total of **24** hours per day.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.011** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.31** pounds per hour, nor more than **0.23** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.11** pounds per hour, nor more than **0.079** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.016** pounds per hour, nor more than **0.012** tons per year.
 - d. The opacity from **PF1.011** shall not equal or exceed **20** percent.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.011** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.011** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.011** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
 - f. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform **monthly** periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expediently as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

J. Emission Unit PF1.012

System 10 – Sand Screen Stockpile Discharge		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.012	Conveyor C-5 transfer to Sand Stockpile	4,369,129	344,806

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.012 has no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.012** shall not exceed **50.0** tons of **Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.012** may operate a total of **24** hours per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.012** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.15** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.055** pounds per hour, nor more than **0.040** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0083** pounds per hour, nor more than **0.0061** tons per year.
 - d. The opacity from **PF1.012** shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.012** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.012** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

K. Emission Units PF1.013 through PF1.015

System 11 – Sand Loading (North)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.013	Front Loader transfer to Sand Feed Bin	4,369,142	344,836
PF1.014	Sand Feed Bin transfer to Sand Conveyor C-2	4,369,142	344,836
PF1.015	Sand Conveyor C-2 transfer to Weigh Hopper	4,369,144	344,831

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.013 through PF1.015, each, have no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.013 through PF1.015, each**, shall not exceed **50.0** tons of **Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.013 through PF1.015, each**, may operate a total of **4** hours per day.
 - (2) **PF1.013 through PF1.015, each**, may operate a total of **1,460** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.013 through PF1.015, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.15** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.055** pounds per hour, nor more than **0.040** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0083** pounds per hour, nor more than **0.0061** tons per year.
 - d. The opacity from **PF1.013 through PF1.015, each**, shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.013 through PF1.015, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.013 through PF1.015, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

L. Emission Units PF1.016 through PF1.018

System 12 – Aggregate Loading (North)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.016	Loader transfer to Rock Feed Bin	4,369,135	344,835
PF1.017	Rock Feed Bin transfer to Rock Conveyor C-3	4,369,135	344,835
PF1.018	Rock Conveyor C-3 transfer to Weigh Hopper	4,369,144	344,831

1. Air Pollution Control Equipment (NAC 445B.346(1)) (Federally Enforceable SIP Requirement)
PF1.016 through PF1.018, each, have no add-on controls.
2. Operating Parameters (NAC 445B.346(1)) (Federally Enforceable SIP Requirement)
 - a. The maximum allowable throughput rate for **PF1.016 through PF1.018, each**, shall not exceed **50.0** tons of **Aggregate** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.016 through PF1.018, each**, may operate a total of **4** hours per day.
 - (2) **PF1.016 through PF1.018, each**, may operate a total of **1,460** hours per year.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (Federally Enforceable SIP Requirement)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.016 through PF1.018, each**, the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.15** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.055** pounds per hour, nor more than **0.040** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0083** pounds per hour, nor more than **0.0061** tons per year.
 - d. The opacity from **PF1.016 through PF1.018, each**, shall not equal or exceed **20** percent.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (Federally Enforceable SIP Requirement)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.016 through PF1.018, each**, on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.016 through PF1.018, each**, on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

M. Emission Unit PF1.019

System 13 – Weigh Hopper (North)		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.019	Weigh Hopper transfer to Charge Conveyor Belt C-1	4,369,144	344,831

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
Emissions from **PF1.019** shall be controlled by **water sprays**.
2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.019** shall not exceed **50.0** tons of **Aggregate and Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.019** may operate a total of **4** hours per day.
 - (2) **PF1.019** may operate a total of **1,460** hours per year.
3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.019** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.038** pounds per hour, nor more than **0.027** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.014** pounds per hour, nor more than **0.010** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0021** pounds per hour, nor more than **0.0015** tons per year.
 - d. The opacity from **PF1.019** shall not equal or exceed **20** percent.
4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.019** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.019** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
 - f. Conduct and record an observation of visible emissions (excluding water vapor) on **PF1.019** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
 - g. The Permittee of any affected facility that uses wet suppression to control emissions from the affected facility must perform **monthly** periodic inspections to check that water is flowing to discharge spray nozzles in the wet suppression system. The Permittee must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if the Permittee finds that water is not flowing properly during an inspection of the water spray nozzles. The Permittee must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

N. Emission Unit PF1.020

System 14 – Charge Conveyor Discharge		Location UTM (Zone 11, NAD 83)	
		m North	m East
PF1.020	Charge Belt Conveyor C-1 Discharge to Truck	4,369,137	344,839

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
PF1.020 has no add-on controls.

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **PF1.020** shall not exceed **50.0** tons of **Aggregate and Sand** per any one-hour period averaged over a daily basis, nor more than **73,000.0** tons per year.
 - b. Hours
 - (1) **PF1.020** may operate a total of **4** hours per day.
 - (2) **PF1.020** may operate a total of **1,460** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B.22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.020** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.15** pounds per hour, nor more than **0.11** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.055** pounds per hour, nor more than **0.040** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0083** pounds per hour, nor more than **0.0061** tons per year.
 - d. The opacity from **PF1.020** shall not equal or exceed **20** percent.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the throughput for **PF1.020** on a daily basis.
 - b. Monitor and record the hours of operation for **PF1.020** on a daily basis.
 - c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
 - d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
 - e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

O. Emission Units S2.008 and PF1.021

System 15 – Cement Silo (North)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.008	Cement Silo Loading	4,369,137	344,839
PF1.021	Cement Silo Discharge to Truck	4,369,137	344,839

1. Air Pollution Control Equipment (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. Emissions from **S2.008** shall be controlled by a **Baghouse**.
 - b. **PF1.021** has no add-on controls.
 - c. Descriptive Stack Parameters for S2.008
 Stack Height: 52.0 feet
 Stack Diameter: 0.5 feet
 Stack Temperature (°F): ambient
 Exhaust Flow: 116.7 dry standard cubic feet per minute (dscfm)

2. Operating Parameters (NAC 445B.346(1)) (*Federally Enforceable SIP Requirement*)
 - a. The maximum allowable throughput rate for **S2.008** shall not exceed **35.0** tons of **Cement** per any one-hour period, nor more than **12,775.0** tons per year.
 - b. The maximum allowable throughput rate for **PF1.021** shall not exceed **5.0** tons of **Cement** per any one-hour period, nor more than **3,650.0** tons per year.
 - c. Hours
 - (1) **S2.008** may operate a total of **1** hour per day.
 - (2) **S2.008** may operate a total of **365** hours per year.
 - (3) **PF1.021** may operate a total of **2** hours per day.
 - (4) **PF1.021** may operate a total of **730** hours per year.

3. Emission Limits (NAC 445B.305, NAC 445B.346(1), NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 - a. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.008** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.035** pounds per hour, nor more than **0.0063** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.012** pounds per hour, nor more than **0.0022** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.0018** pounds per hour, nor more than **0.00032** tons per year.
 - (4) The opacity from **S2.008** shall not equal or exceed **20** percent.
 - b. The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **PF1.021** the following pollutants in excess of the following specified limits:
 - (1) The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **5.59** pounds per hour, nor more than **2.04** tons per year.
 - (2) The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **1.55** pounds per hour, nor more than **0.57** tons per year.
 - (3) The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.23** pounds per hour, nor more than **0.086** tons per year.
 - (4) The opacity from **PF1.021** shall not equal or exceed **20** percent.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

O. Emission Units S2.008 and PF1.021 (continued)

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346(2)) (*Federally Enforceable SIP Requirement*)

The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.

- a. Monitor and record the throughput for **S2.008 and PF1.021, each**, on a daily basis.
- b. Monitor and record the hours of operation for **S2.008 and PF1.021, each**, on a daily basis.
- c. Record the corresponding average hourly throughput rate in tons per hour. The average hourly throughput rate shall be determined from the total daily throughput and the total daily hours of operation.
- d. Monitor and record the total yearly throughput rate in tons per year. The annual throughput shall be determined as the sum of the monthly throughput rates for the year for all previous months of that year.
- e. Monitor and record the total yearly hours of operation per year. The annual hours of operation shall be determined as the sum of the monthly hours of operation for all previous months of that year.
- f. Conduct and record an observation of visible emissions (excluding water vapor) on the **Baghouse** controlling **S2.008** on a **monthly** basis while operating. The observer shall stand at a distance sufficient to provide a clear view of the emissions with the sun oriented to their back. If visible emissions are observed and exceed the applicable opacity standard, the Permittee shall take immediate corrective action. The Permittee shall maintain in a contemporaneous log with the following recordkeeping: the calendar date and time of any required monitoring, name of the observer, results of the monthly observation of visible emissions, and any corrective actions taken.
- g. Inspect the **Baghouse** installed on **S2.008** in accordance with the manufacturer's operation and maintenance manual and record the results (e.g. the condition of the filter fabric) and any corrective actions taken.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

P. Emission Unit S2.010

System 16 – Diesel Generator (Sand Screen)		Location UTM (Zone 11, NAD 83)	
		m North	m East
S2.009	50 Hp Diesel Generator, Deutz Engine, Serial #: 790502, Year: 1980. Replaced with S2.010, Air Case 12163)	4,369,119	344,828
S2.010	165 HP MQ Power Diesel Generator for Sand Screen Plant (John Deere engine, mdl# 6068TF275, mfd 2005, EPA Tier II)	4,369,119	344,828

1. Air Pollution Control Equipment (NAC 445B.346.1) (*Federally Enforceable SIP Requirement*)
 - a. **S2.010** has no add-on controls.
 - b. Descriptive Stack Parameters
 Stack Height: 7.0 feet
 Stack Diameter: 0.375 feet
 Stack Temperature: 1040 °F

2. Operating Parameters (NAC 445B.346.1) (*Federally Enforceable SIP Requirement*)
 - a. **S2.010** may consume only **diesel**.
 - b. The maximum allowable fuel consumption rate for **S2.010** shall not exceed **8.3 gallons** per any one-hour period.
 - c. Hours
 (1) **S2.010** may operate a total of **24** hours per day.

3. Emission Limits (NAC 445B.305, NAC 445B.346.1, NAC 445B. 22017) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon issuance of this operating permit, shall not discharge or cause the discharge into the atmosphere from **S2.010** the following pollutants in excess of the following specified limits:
 - a. The discharge of **PM** (particulate matter) to the atmosphere shall not exceed **0.081** pounds per hour, nor more than **0.36** tons per year.
 - b. The discharge of **PM₁₀** (particulate matter less than or equal to 10 microns in diameter) to the atmosphere shall not exceed **0.081** pounds per hour, nor more than **0.36** tons per year.
 - c. The discharge of **PM_{2.5}** (particulate matter less than or equal to 2.5 microns in diameter) to the atmosphere shall not exceed **0.081** pounds per hour, nor more than **0.36** tons per year.
 - d. The discharge of **SO₂** (sulfur dioxide) to the atmosphere shall not exceed **0.33** pounds per hour, nor more than **1.47** tons per year.
 - e. The discharge of **NO_x** (oxides of nitrogen) to the atmosphere shall not exceed **1.79** pounds per hour, nor more than **7.84** tons per year.
 - f. The discharge of **CO** (carbon monoxide) to the atmosphere shall not exceed **1.36** pounds per hour, nor more than **5.94** tons per year.
 - g. The discharge of **VOCs** (volatile organic compounds) to the atmosphere shall not exceed **0.40** pounds per hour, nor more than **1.77** tons per year.
 - h. The opacity from **S2.010** shall not equal or exceed **20 percent**.

4. Monitoring, Recordkeeping, and Reporting (NAC 445B.346.2) (*Federally Enforceable SIP Requirement*)
 The Permittee, upon the issuance of this operating permit, shall maintain, in a contemporaneous log, the monitoring and recordkeeping specified in this section. All records in the log must be identified with the calendar date of the record. All specified records shall be entered into the log at the end of the shift, end of the day of operation, or the end of the final day of operation for the month, as appropriate.
 - a. Monitor and record the total daily hours of operation for **S2.010** for each day of operation.
 - b. Monitor and record the consumption rate of **diesel** on a daily basis for **S2.010** (in **gallons**) by multiplying the maximum hourly fuel consumption rate as stated in **P.2.b** of this section and the total daily hours of operation.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

P. Emission Unit S2.010 (continued)

5. Federal Requirements (NAC 445B.346.2) (*Federally Enforceable SIP Requirement*)
National Emissions Standards for Hazardous Air Pollutants (NESHAP) – 40 CFR Part 63 Subpart ZZZZ – for Stationary Reciprocating Internal Combustion Engines
 - a. Emissions Limitations, Management Practices and Other Requirements (40 CFR 63.6603(a), Table 2d)
The Permittee must comply with the following requirements, except during periods of startup:
 - (1) Change oil and filter every 1,000 hours of operation or annually, whichever comes first;
 - (2) Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; and
 - (3) Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.
 - b. Monitoring, Installation, Collection, Operation, Maintenance Requirements (40 CFR 63.6625)
 - (1) The Permittee must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions. (40 CFR 63.6625(e))
 - (2) The Permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in **P.5.a** of this section. (40 CFR 63.6625(h))
 - (3) The Permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in **P.5.a.(1)** of this section. The oil analysis must be performed at the same frequency specified for changing the oil in **P.5.a.(1)** of this section. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the Permittee is not required to change the oil. If any of the limits are exceeded, the Permittee must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the Permittee must change the oil within 2 business days or before commencing operation, whichever is later. The Permittee must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. (40 CFR 63.6625(i))
 - c. Compliance Requirements (40 CFR 63.6605, 63.6640, Table 6)
 - (1) The Permittee must be in compliance with the emission limitations, operating limitations, and other requirements in Subpart ZZZZ that apply at all times. (40 CFR Part 63.6605(a))
 - (2) The Permittee must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the Permittee to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source. (40 CFR Part 63.6605(b))
 - (3) The Permittee must also report each instance in which they did not meet the requirements in Table 8 to Subpart ZZZZ that apply.
 - (4) Permittee must demonstrate continuous compliance with each emission limitation, operating limitation, and other requirements in Table 2d to Subpart ZZZZ that applies to the Permittee according to methods specified below: (40 CFR 63.6640(a), Table 6)
 - (a) Operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or
 - (b) Develop and follow Permittee's own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section V. Specific Operating Conditions (continued)

P. Emission Unit S2.010 (continued)

5. Federal Requirements (NAC 445B.346.2) (*Federally Enforceable SIP Requirement*)
National Emissions Standards for Hazardous Air Pollutants (NESHAP) – 40 CFR Part 63 Subpart ZZZZ – for Stationary Reciprocating Internal Combustion Engines (continued)
 - d. Recordkeeping Requirements (40 CFR Part 63.6655)
The Permittee must keep the following records:
 - (1) A copy of each notification and report that the Permittee submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirement in 40 CFR Part 63.10(b)(2)(xiv). (40 CFR 63.6655(a)(1))
 - (2) Records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. (40 CFR 63.6655(a)(2))
 - (3) Records of performance tests and performance evaluations as required in 40 CFR Part 63.10(b)(2)(viii). (40 CFR 63.6655(a)(3))
 - (4) Records of all required maintenance performed on the RICE and any air pollution control and monitoring equipment. (40 CFR 63.6655(a)(4))
 - (5) Records of actions taken during periods of malfunction to minimize emissions in accordance with **P.5.c.(2)** of this section including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.
 - (6) The Permittee must keep the records required in with **P.5.c.(3)** of this section to show continuous compliance with each emission or operating limitation that applies. (40 CFR 63.6655(d))
 - (7) The Permittee must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that the Permittee operated and maintained the stationary RICE and after-treatment control device (if any) according to their own maintenance plan. (40 CFR 63.6655(e))

******End of Specific Operating Conditions******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section VI. Emission Caps

A. Not Applicable

******End of Emission Caps******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section VII. Surface Area Disturbance Conditions

The surface area disturbance for **Allen Road Plant** is **18** acres.

A. Fugitive Dust (NAC 445B.22037) (*Federally Enforceable SIP Requirement*)

1. No person may cause or permit the handling, transporting or storing of any material in a manner which allows or may allow controllable particulate matter to become airborne.
2. Except as otherwise provided in subsection 4, no person may cause or permit the construction, repair, demolition, or use of unpaved or untreated areas without first putting into effect an ongoing program using the best practical methods to prevent particulate matter from becoming airborne. As used in this subsection, “best practical methods” includes, but is not limited to, paving, chemical stabilization, watering, phased construction and revegetation.
3. Except as otherwise provided in subsection 4, no person may disturb or cover 5 acres or more of land or its topsoil until he has obtained an operating permit for surface area disturbance to clear, excavate, or level the land or to deposit any foreign material to fill or cover the land.
4. The provisions of subsections 2 and 3 do not apply to:
 - a. Agricultural activities occurring on agricultural land; or
 - b. Surface disturbances authorized by a permit issued pursuant to NRS 519A.180 which occur on land which is not less than 5 acres or more than 20 acres.

*****End of Surface Area Disturbance Conditions*****



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section VIII. Schedules of Compliance

A. Not Applicable

******End of Schedule of Compliance ******



Bureau of Air Pollution Control

Facility ID No. A0903

Draft Permit No. AP3273-3931.01

CLASS II AIR QUALITY OPERATING PERMIT

Issued to: HISKETT & SONS, LLC – ALLEN ROAD PLANT (AS PERMITTEE)

Section IX. Amendments

Month Day, Year (Air Case #12163)

- Systems 01-02-03-06: Revise operating hours, throughputs, and emissions.
- System 04: Revise operating hours, control type, and emissions.
- System 05: Revise operating hours, system name, control type, material type, and emissions.
- System 07: Revise operating hours, propane usage, emissions.
- System 08-09-10: Revise operating hours.
- System 16: Replace 50 HP diesel engine with a 165 HP diesel engine.

This permit:

1. **Is non-transferable. (NAC 445B.287.3) (Federally Enforceable SIP Requirement)**
2. **Will be posted conspicuously at or near the stationary source. (NAC 445B.318.5) (Federally Enforceable SIP Requirement)**
3. **Will expire and be subject to renewal five (5) years from: March 19, 2024 .**
(NAC 445B.315) (Federally Enforceable SIP Requirement)
4. **A completed application for renewal of an operating permit must be submitted to the Director on the form provided by him with the appropriate fee at least 70 calendar days before the expiration date of this operating permit. (NAC 445B.3473.2) (Federally Enforceable SIP Requirement)**
5. **Any person aggrieved by a final decision of the Department may, not later than 10 days after notice of the action of the Department, appeal the decision by filing a request for a hearing before the Commission on a form 3* with the State Environmental Commission, 901 South Stewart Street, Suite 4001, Carson City, Nevada 89701-5249. *(See adopting agency for form.) (NAC 445B.890) (State Only Requirement)**

THIS PERMIT EXPIRES ON: March 19, 2029

Signature: _____

Issued by: XXXXXXXXXXXX
Supervisor, Permitting Branch
Bureau of Air Pollution Control

Phone: (775) 687-XXXX **Date:** TBD

Class II Insignificant Activities List
Appended to Permit #AP3273-3931.01

Emission Unit #	Emission Unit Description
None Listed	